

CARRIER Performance

Multizone All Ducted

AHRI Cert #: **204707613**

Outdoor Unit #: **38MGRQ24C--3**

Indoor Unit #:

🔥 Maximum Heating Capacity (Btu/hr) @5°F: **23,370**

🔥 Rated Heating Capacity (Btu/hr) @47°F: **24,000**

❄️ Rated Cooling Capacity (Btu/hr) @95°F: **24,000**

Information Tables

Brand	CARRIER
Series	Performance
Ducting Configuration	Multizone All Ducted
AHRI Certificate No.	204707613
Outdoor Unit #	38MGRQ24C--3
Indoor Unit Type	Ducted Indoor Units
Indoor Unit #	
Furnace Unit #	
SEER	21
EER	11
HSPF Region IV	10
Energy Star	
Variable Capacity	✓
Maintenance Capacity (Max 5°F/Max 47°F)	65%
Maintenance Capacity (Max 5°F/Max 17°F)	94%
Maintenance Capacity (Max 5°F/Rated 47°F)	97%
Integration	Works with 24V interface and third party thermostat
Connectivity	Wifi capable
Operational Diagnostics	
Refrigerant(s)	R410A

Pan Heater

Type	Integrated
Input Power	150.0
Model #	

Operation 1.When the unit power on and changed in heating mode,and if the outdoor temperature continue lower than 3C for 30 seconds,after running for 25mins, the base pan heater will be activated for 5 minutes. 2.If be on the defrost mode and the outdoor temperature lower 1C for 10 seconds the base pan heater will be activated and will be 5 mins delay inactive after defrost.

Performance Specs

Heating / Cooling	Outdoor Dry Bulb	Indoor Dry Bulb	Unit	Min	Rated	Max
Heating	5°F	70°F	Btu/h	4,908	-	23,370
			kW	0.8	-	3.79
			COP	1.8	-	1.81
Heating	17°F	70°F	Btu/h	5,214	17,600	24,830
			kW	0.59	1.42	2.83
			COP	2.59	3.63	2.57
Heating	47°F	70°F	Btu/h	7,512	24,000	35,770
			kW	0.65	1.62	3.09
			COP	3.39	4.34	3.39
Cooling	82°F	80°F	Btu/h	7,014	-	33,400
			kW	0.51	-	2.45
			COP	4.03	-	4
Cooling	95°F	80°F	Btu/h	6,185	24,000	29,450
			kW	0.64	1.76	3.03
			COP	2.83	4	2.85