



Project/Job Name: _____
 Location: _____
 Fixture Type: _____
 Notes: _____

S13511 - 24 Watt Commercial LED Downlight; 6 in.; Remote Driver; Watt and Color Selectable; 120-347 Volt

- Wattage Selectable
- CCT Selectable
- IC Rated
- Air Tight
- Flicker Free



ELECTRICAL

Technology:	LED
Watts:	24W/16W/12W
Volts:	120V-347V
Lumens:	2000L/1500L/1100L
CRI:	90+
CCT (Kelvins):	27K/30K/35K/40K/50K - Warm White to Natural Light
Beam Spread :	90
Hours Rated:	50000
Dimmable:	Yes-Dimmable - 0-10V Dimming
Dimmable Down To %:	100 to 10 percent
Incandescent Equivalent :	100W
Operating Temperature :	-25C (-13F) to +40C (+104F)
Replaceable Light Source :	No
Connection:	Hardwire
THD:	<30%
Power Factor :	>0.9
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923135118
Each Quantity:	1
Each Dimensions:	9.45 x 3.46 x 8.07

INFO

Specification Note:	Default Wattage: 24W; FT6 cable between driver and lighting head; Default CCT: 3000K
---------------------	--

PHYSICAL

Finish:	Matte White
Lens Finish:	Frosted
Lens Material:	Polycarbonate (PC)
Dimensions:	H:2.84" DIA:7.36"
Weight (Lbs.):	0.95
Material:	Aluminum












INSTALLATION

Sloped Ceiling Compatible:	No
----------------------------	----

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor and Outdoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	4515180
Energy Star Lamp Category:	Downlight Recessed
CA Prop 65:	Lead
Vapor Tight Fixture Rated:	No
ADA Compliant:	No
Closet Rated:	No
FCC Compliant:	Yes
IP Rating:	IP54
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions

ACCESSORIES

	80-866	6-Inch Asymmetric New Construction Recessed Downlight Mounting Plate; Flat
	80-867	Universal New Construction Recessed Downlight Mounting Plate; Flat; 3.5-Inch; 4-Inch; 6-Inch; 8-Inch
	80-944	New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/Joist mounting of 6-inch Recessed Downlights; Up to 6.25-inch hole diameter
	80-952	New Construction Mounting Plate for Stud/Joist mounting of 6-inch Recessed Downlights; Up to 6.5-inch hole diameter
	80-959	Rough-In Mounting Plate for 4/6/8 or 10 in. Commercial Downlight Fixtures
	80-985	6 FOOT REMOTE DRIVER 3-PIN EXT
	80-997	Downlight Hanger Bar Kit; For Asymmetrical Plates; New Construction
	S13525	Accessory for CDL Remote Driver - 6in rd matte clear/white trim
	S13526	Accessory for CDL Remote Driver - 6in rd matte clear trim
	S13527	Accessory for CDL Remote Driver - 6in rd matte black trim
	S13541	6" Flat Goof Ring for Commercial Downlights, Round, White Finish, 10.00 OD, 6.00 ID, 0.032 Thick.