

INSTALLATION INSTRUCTIONS

LED CEILING FIXTURE

120VAC Input, Dimmable

READ AND FOLLOW SAFETY INFORMATION

CAUTION - Turn off the main power at the circuit breaker before installing and servicing the fixture to prevent possible injury from electric shock.

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections, obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

INSTALLATION & ASSEMBLY

1. Push in the direction of the arrow (which attached to the fixture base (4)) to remove the mounting bracket (2). Pull the supply wires (5 & 6) and house ground wire (7) out from outlet box (1). Make four holes locations on the wall that align with the hole distance in mounting bracket (2). Drill four holes with 5/16" size drill bit at the marked locations. Insert drywall anchors (12) into each drilled mounting hole.
2. Attach the mounting bracket (2) to the outlet box (1) with two mounting screw (3). Attach the mounting bracket (2) to the drywall anchor using four drywall anchor screws (13).
3. Connect the power supply wires to the fixture lead wires by connecting the black fixture wire (9) to the black supply wire (6), and the white fixture wire (8) to the white supply wire (5) using wire connector (11). Connect the fixture ground wire (10) to the house ground wire (7) by fixed on the mounting bracket (2).
4. Carefully tuck all wiring back into the outlet box (1).
5. Color Temperature Switchable: Could change colors easily by switching the button on fixture base (4) to select colors from 2700K to 3000K to 4000K to 5000K and 6500K.

6. Final assembly - Hang the hook (14) with the fixture base (4), and then aim the fixture base (4) to the snap position and push it to the right until all clips (15) on the fixture base (4) slide into the mounting bracket (2) and are secured in place.
7. Installation complete, restore power at the circuit breaker and turn light switch on to activate this fixture.

