



PREPARATION before INSTALLATION:

1. If an existing fixture is being replaced, remove it and note to which wire in the outlet box the original fixture was attached.
2. Before discarding the carton, double-check the packaging to make sure all parts have been found.
3. This fixture was designed to be mounted on an octagon outlet box. The box must be securely mounted to the structure of the building.

IMPORTANT:

1. **WARNING** - Disconnect power before relamping or wiring the fixture. Turn off the entire electrical circuit to which the lighting fixture is attached.
2. Installation and maintenance of this fixture should be completed by a licensed electrician.
3. Failure to install the fixture correctly could result in serious injury or death.
4. Read all instructions before starting installation.

INSTALLATION STEPS:

1. Fix the hanging ring to the lamp body.
2. Connect the fixture hanging ring and the straight mounting bracket with the lamp threaded rod.
3. Fix the straight mounting bracket to the junction box with screws.
4. Connect the wires using wire connectors as follow:
 BLACK wire to home LIVE wire.
 WHITE wire to home NEUTRAL wire.
 NOTE: Ensure the bare wire is NOT exposed to prevent electrical leakage. Secure the ground wire and external ground wire to the mounting bracket using green screws.
5. Cover the wiring with the canopy and fix it with decorative ring.
6. Install the light bulb(not included).
7. Screw the globe glass to cover the bulb.