

ARRIVE

Project:

Fixture Type: Location:

Contact:

LED Wall Mount • Wet Location



P6067-3130K9

Specifications:

Description:

The P6067 features a 120V alternating current (AC) source which eliminates the need for a traditional LED driver.

Construction:

- Powdercoated Black (-31)
- Die-cast aluminum construction
- LED Module is replaceable (part # 93054049)
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- CA Title 24 Compliant
- Covers a standard 4" recessed outlet boxMounting strap for outlet box included

Images:



Dimensions:

A	В
6"	8-3/4"

Extends H/CTR 7-3/8" 4"



Performance:

Number of Modules	1
Input Power	9W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	623/69 (LM-79) per module
CCT	3000K
CRI	90
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 yrs.
Labels	cCSAus certified for wet locations ENERGY STAR [®] qualified

Catalog number:

Base	Finish	Color Temp	CRI
P6067	31 - Black	30K - 3000K	9 - 90 CRI



ARRIVE

LED Wall Mount • Wet Location



P6067-3130K9

Dimming Notes:

P6067 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls. The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300P)
Lutron	Nova T Series	(Part Number NTELV-300)
Lutron	Vierti Series	(Part Number VTELV-600)
Lutron		(Part Number AYCL-153P)
Lutron		(Part Number DVCL-153P)
Lutron		(Part Number MAELV-600)
Lutron		(Part Number SPELV-600)
Leviton		(Part Number AWRMG-EAW)
Leviton		(Part Number 6615-P)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.