# **AVIATOR 5**

# FR-W1811-5

54" Ceiling Fan

# DERN FORMS



#### PRODUCT DESCRIPTION

Inspired by the golden age of flying, this smart fan takes technology to the next level. Pair it with the exclusive Modern Forms app to save on energy costs and intuitively create schedules that adapt to your behavior. Two simulated wood finishes contrast with the matte black or graphite housings for an understated look in interior or exterior spaces. Available option LED light kit sold separately.

#### **FEATURES**

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED luminaire sold separately (F-1811-5-LED-\*\*)
- Includes BT remote control (MB and GH/WG still come with a wall control)
- Optional wall control sold separately
- Compatible with Modern Forms app

#### **AIRFLOW/ENERGY EFFICIENCY**

Weighted-Average/High Airflow CFM: 5638/8418 Weighted-Average/High Energy Use (W): 24/34 Estimated Yearly Energy Cost (\$): Weighted-Average/High Efficiency (CFM/W): 233/238 Max RPM: 161

#### WIRELESS PERFORMANCE


Up to 150 ft\* Wi-Fi Range: **Bluetooth Range:** Up to 150 ft\*

#### **ORDER NUMBER**

Model	Housing	Blade				
FR-W1811-5	GH Graphite MB Matte Black MB Matte Black	WG Weathered Gray DK Distressed Koa MB Matte Black				

Example: FR-W1811-5-MB/DK

- \*Results may vary based on application and surroundings.
- \*This fan comes uni-pack blade select options are not available



#### **SPECIFICATIONS**

**Construction:** Aluminum, ABS Blade: 14° Pitch, 54" sweep Downrod: .75"W x 4.5"H included

**Mounting Slope:** Up to 30° Wire: 80" **Hanging Weight:** 23 lbs **Total Power:** 35W

Standards: UL/cUL Wet Location listed, Title 24 JA8-2016

Compliant, Title 20, Energy Star rated

**Motor Type:** 125 x 20 sensorless DC motor

# **OPTIONAL LUMINAIRE PERFORMANCE**

**Light Source:** LED 19.5W **Light Wattage:** Lumens/Delivered Lumens: 1600/846 **Dimming:** Integrated CRI: 90

**Color Temperature:** 3000K (2700K/3500K options available)

**Rated Life:** 50,000 hours

# **OPTIONAL LUMINAIRE (Sold Separately)**

Model	Finish		
F-1811-5-LED	GH MB	Graphite Matte Black	

Example: F-1811-5-LED-GH



The Modern Forms app synchronizes seamlessly with smart home devices you already own













modernforms.com Phone (800) 526.2588 (800) 526.2585

Headquarters/Eastern Distribution Center Central Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

# **AVIATOR 5**

FR-W1811-5

54" Ceiling Fan



# **OPTIONAL ACCESSORIES**

OF HONAL ACCESSORIES				
Bluetooth Wall Control		F-WCBT	<b>WT</b> White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.
Bluetooth Remote Control	MACCOUNT O	F-RCBT	<b>WT</b> White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with Moder Forms Smart Fans. Includes easy-to-install wall cradle and batteries.
Downrod		XF-12 12IN XF-18 18IN XF-24 24IN XF-36 36IN XF-48 48IN XF-60 60IN XF-72 72IN		All our downrods are .75 (in) and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers		XF-I		Connects two downrods together.
Sloped Ceiling Kit		XF-SCK		Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: Wall Control: F-WCBT-WT, Remote Control: F-RCBT-WT, Downrod: XF-12-BN, Downrod Coupler: XF-I-MB, Sloped Ceiling Kit: XF-SCK-MW

# SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

# **SLOPED CEILING DEGREE CONVERSION CHART**

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to  $30^{\circ}$  (7/12 pitch). Optional slope kit allows mounting on ceilings up to  $45^{\circ}$  (12/12 pitch). The receiver will mount inside canopy up to  $45^{\circ}$ .

NOTE: Recommended maximum downrod length of 72" with 80" lead wire