

roject:		
ixture Type:		
ocation:		
Contact:		

LED RECESSED

Ceiling mounted · Wet location listed





Specifications:

Description:

5" LED Round Retrofit, 600 lumens

Construction:

Antique Bronze (-20) Steel construction

Glass: White polycarbonate lens

Flicker-free dimming to 10% brightness with most ELV type dimmers

(See Dimming Notes)

Title 24 compliant

covers a standard 4" hexagonal recessed outlet box

Mounting strap for outlet box included

6" of wire supplied

Antique Bronze finish

Flicker free dimming down to 10%

Flicker rate less than 30%

Frosted polycarbonate lens

Performance:

Number of Modules	1	
Input Power	10.5W	
Input Voltage		
Input Frequency		
Lumens/LPW	700/66 (LM-79) per module	
CCT	3000K	
CRI		
Life	(L70/TM-21)	
EMI/RFI	FCC Title 47, Part 15, Class B	
Min. Start Temp	-30° C	
Max. Operating Temp	30° C	
Warranty	5 year warranty	
Labels	cULus Wet location listed	
	ENERGY STAR® qualified	

P8061-20-30K

Images:



Dimensions:

Diameter: 6.34" Height: 3.82"

Catalog number:

 Base
 Finish
 Color Temp
 CRI

 98061
 20 - Antique Bronze
 / 30K - 3000K
 Blank- 90 CRI