ALTERNATING TREAD STAIR - ATS-12-68 APPROX WEIGHT: 278.08 lbs. DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!! ***ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE*** 23 5/8" 23 5/8" 20" 9 3/4" TOP STEP - SCALE: 1:12 185 5/8" STEP - SCALE: 1:12 12 1/4" 10 1/2" 115 3/4" 7 3/16" STEP **HEIGHT SPACING** 143 3/4" TOP STEP HEIGHT 68° 33 3/8" 9 1/8" 65"

68 1/2"

BCN

QUOTED LEAD TIME: X

ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON

FAB.

POWER

DIMENSION TO FRANCE + 1/4'

STANDARD FEATURES			
MODEL NUMBER: ATS-12-68			
CLIMB ANGLE: 68°			
NUMBER OF STEPS: 20			
(INCLUDING TOP STEP)			
TÒP STEP HEIGHT: 143 3/4"			
STEP HEIGHT SPACING: 7 3/	16"		
HANDRAIL HEIGHT: 12 1/4"			
OVERALL HEIGHT: 185 5/8"			
OVERALL LENGTH: 68 1/2"			
OVERALL WIDTH: 23 1/2"			
CHAIN GATES AT TOP STEP			
RUBBER BUMPER STRIP	EOD INITE	DNIAL LISE C	
MAX CAPACITY IS 350 LBS	FOR INTERNAL USE C PROJECT SIGN C		
TOUGH BAKED IN POWDER COATED YELLOW FINISH	SALES		
COATED TELLOW FINISH	ENG.		

SPECIAL FEATURES

NONE

23 1/2"

			DIME	:NSION TOLER	RANCE ± 1/4"	
	A P P R O V	REPR REQUIR (COMP ANI	JINDERSIGNED, AGF ESENTED SATISFIES I EMENTS. I ALSO AC CONFIRM PRODUC' LIANCE WITH ALL A D LOCAL REGULATI DDIFIED UNITS A [] As drawn	DESIGN AND CKNOWLEDG I AND INSTAL PPLICABLE FE ONS AND STA ARE NON-F	DIMENSION SE MY DUTY TO LLATION EDERAL, STATE ANDARDS. RETURNABLE	<u> </u>
	Α	Signed:	Date:			
	L	Printed Na	me:	IPT OF SIGNED	APPROVAL DRAW	ING
DNI Y	DISTRI	IBUTOR'S NAME:			P.O.# _Y	
)FF	٧	ESTIL MA	NUFACTURII	٧G	W.O.# X	

QUOTE #

4/22/2009

SCALE: 1:34

FILE NAME:

44-007-359