ALTERNATING TREAD STAIR - ATS-8-56 APPROX WEIGHT: 208.17 lbs. DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!! ***ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE*** 23 5/8" -9 3/4" 23 5/8" 20" TOP STEP - SCALE: 1:12 STEP - SCALE: 1:12 138 1/4" 10 1/2" 18 5/8' 1/8" 79 3/4" - 7 3/8" STEP HEIGHT **SPACING** 95 7/8" TOP STEP HEIGHT 56° 27 3/8"

69"

73 1/2"

ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON

DIMENSION TOLERANCE ± 1/4" POWER

FOR INTERNAL USE ONLY PROJECT SIGN OFF

SALES ENG.

FAB.

STANDARD FEATURES
MODEL NUMBER: ATS-8-56
CLIMB ANGLE: 56°
NUMBER OF STEPS: 13
(INCLUDING TOP STEP)
TOP STEP HEIGHT: 95 7/8"
STEP HEIGHT SPACING: 7 3/8"
HANDRAIL HEIGHT: 18 5/8"
OVERALL HEIGHT: 138 1/4"
OVERALL LENGTH: 73 1/2"
OVERALL WIDTH: 23 1/2"
CHAIN GATES AT TOP STEP

9 1/8"

23 1/2"

CHAIN GATES AT TOP STEP RUBBER BUMPER STRIP

MAX CAPACITY IS 350 LBS TOUGH BAKED IN POWDER COATED YELLOW FINISH

SPECIAL FEATURES NONE

	DIVIDION TOLEN TICE = 1/4
A P P R O V	I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS. ANY MODIFIED UNITS ARE NON-RETURNABLE [] As drawn [] As marked
A	Signed:Date:
ᅵ┖	Printed Name:
	LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWIN
	la a "

LLAD TIME WILL START OF	ON NEGET	TOT SIGNED	ALL NOVAL DIVAVIIN
DISTRIBUTOR'S NAME:	P.O.# X		
VESTIL MANUFAC	W.O.# X		
B.WOOD	DATE: 4/2	.2/2009	SALES: X
eference: X		SCALE: 1:30	
QUOTED LEAD TIME: X	QUOTE #		44-007-244