

WALL LANTERN

Assembly Instructions

CAUTION



• Inspect the wire insulation for any cuts, abrasions, or exposed copper that may have resulted during shipping. If there is a defect in the wire, do not attempt installation.

• Before starting installation of this fixture or removal of a previous fixture, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box.

TOOLS REQUIRED



Ladder



Safety glasses



Electrical tape




Phillips screwdriver




Flat blade screwdriver




Pliers




Wire strippers



Fixture




Glass frame



Mounting Unit



Wire Nuts



Mounting Screws



screw



Cap Nut


*PARTS SHOWN MAY DIFFER SLIGHTLY PER LIGHT FIXTURE

WALL LANTERN

Assembly Instructions

STEP 1

Use the mounting screws to attach the mounting unit to the junction box



STEP 2



Make the electrical connection from the junction box to the fixture. Connect the ground wire to the mounting unit using the preinstalled green ground screw. Then, connect the positive, negative and ground wires with the supplied wire nuts. Secure with electrical tape

Connect Clear, Brown, Gold or Black Parallel Wire without tracer (round & smooth) or Black Fixture Wire to:

Black or Red Supply Wire or Insulated Wire (other than green) with copper conductor.


Connect Clear, Brown, Gold or Black *Parallel Wire with tracer (square & ridged) or White Fixture Wire to:

White Supply Wire or Insulated Wire (other than green) with silver conductor




Step 3

Place the canopy on the mounting unit, then Fix the Cap Outside screws.




Step 4

Unscrew the screws and remove the base metal ...



Step 5

Place the glass frame into the fixture, insert the metal frame, and tighten the screws to secure it.



STEP 6

Install bulb(Not Included)
E26 Type A bulb

