



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11296 - 15 Watt; LED Gimbaled Downlight; 6 Inch; RGB & Tunable White; Round; Starfish IOT; Black Finish; 1200 Lumens; 120-277 Volt

- Air Tight
- Has Driver
- IOT Enabled
- CCT Selectable
- IC Rated



ELECTRICAL

Technology:	LED
Watts:	15W
Volts:	120V-277V
Lumens:	1200L
CRI:	90
CCT (Kelvins):	2700K-5000K
Color Description:	Warm to Cool White/Color Changeable
Beam Spread :	36
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	Only with Starfish App
Incandescent Equivalent :	75W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Replaceable Light Source :	No
Number of LEDs :	36
Connection:	Direct Wired
Power Factor :	>0.9
Voltage Type:	Range Voltage
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923112966
Each Quantity:	1
Each Dimensions:	8.19 x 3.94 x 8.27
Case UPC:	10045923112963
Case Quantity:	12
Case Dimensions:	17.32 x 12.60 x 17.32

INFO

Specification Note:	360 degree rotation; 0 to 80 degree aiming angle
---------------------	--

PHYSICAL

Finish:	Black
Lens Finish:	Frost
Lens Material:	Plastic
Finish Family:	Black
Dimensions:	H:2.13" DIA:7.48"
Weight (Lbs.):	1.22
Material:	Aluminum

INSTALLATION

Max Drywall Thickness:	1 in.
Rec. Spacing Between Fixtures:	3 ft. to 4 ft.
Clearance Height:	3

IOT

IOT Enabled:	Yes
What's Supported:	Google Home;Alexa;Siri;SmartThings

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2470770
Energy Star Lamp Category:	Downlight Recessed
CA Prop 65:	Lead
FCC Compliant:	Yes
IP Rating:	IP42
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
Restrictions:	No Restrictions

ACCESSORIES

**80-944**New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/Joist mounting of 6-inch Recessed Downlights: Up to 6.25-inch hole diameter

**80-949**6 FOOT REMOTE DRIVER 1-PIN EXT

**80-951**New Construction Mounting Plate for Stud/Joist mounting of 6-inch Recessed Downlights; Up to 5.688-inch hole diameter

**86-216**Temporary work light; LED; For use with remote drivers; Low voltage 10W/12W/24W; 3000K; 12 Volts
