


# **DESIGNER SERIES WALL MOUNT HOOD SPECIFICATIONS**

### JDH242/C2

Halogen lights. This model is not available with heat lamps.


## **Dimensional Information**

Width	42
Depth	24.0
Height	30.0
CFM @ 0.0" SP	600.0
Sones	6.5
Amps	4.4
# Lights	3.0




# Wall Side S 1/2" S 1/4" Vent Holes Electrical Centerline of Hood

600 CFM B200 Dual Blower (Top View)



# Recommended Mounting Height\*



\*Exceeding recommended mounting height may compromise performance.

## **Electrical/Mechanical Specifications For Blower Unit**

			•								
Model	Volts	Amps*	Hz	RPM	CFM SP@0.0"	Equivalent CFM	CFM SP@0.1"	CFM SP@0.2"	CFM SP@0.3"	Minimum Round Duct Size	Sones#
B200 Dual	115.0	2.9	60.0	1550.0	600.0	900.0	531.0	480.0	430.0	8" (50 sq. in.)	6.5

<sup>+</sup> This model is equipped with halogen lighting: (2 lights: 30" - 41", 3 lights: 42" - 48").



<sup>\$</sup> Because the Magic Lung® blower uses centrifugal filtration rather than conventional baffle or mesh filters, the Magic Lung® blower can handle cooking equipment with higher cubic feet per minute (CFM) requirements and can deliver equivalent CFM much more efficiently than other filtration systems. When comparing the Magic Lung® with other blower units made by other manufacturers, use the "Equivalent CFM".

<sup>#</sup> Ratings in accordance with the Standard Test Code by the Energy Systems Laboratory of the Texas Engineering Experiment Station.