

4 Assembly instructions

See image 2

a	Fix the front cloth and then the front basket
---	---

5 Operation Guide

5.1 Choice of the gas cylinder, regulator and hose

1. Choice of Gas Cylinder

For a gas BBQ over 10 KW, you can use for example a 10 or 10.5 kg gas cylinder.

- The maximum diameter is: in Germany, 5 kg is 230 mm, 10 kg 300 mm;
- The Maximum height (regulator included) is: in Germany, 5 kg is 460 mm, 10 kg is 575 mm;
- Please consult your local gas cylinder supplier to know the right maximum size.

2. Choice of Gas Type

You can choose:

- Propane (suitable for conditions down to -44° Celsius)
- Butane (suitable for conditions above 5° Celsius, but cheaper than propane)
- LPG (a mixture of Propane and Butane, the percentage depends on local conditions)

3. Choice of Regulator

Once you have chosen your gas type, match the type of gas regulator you purchase, please check the technical information chapter in this manual: Gas pressure. The gas hose you need is country specific and should be bought locally. Please consult your local Gas dealer for advice.

Country	Gas type and pressure
UK, France, Spain, Portugal, Belgium, Ireland, Greece, Luxembourg, Italy, Switzerland	I3+(28-30/37)
Denmark, Sweden, Norway, Finland, Iceland, The Netherlands, Hungary, Czech Republic	I3B/P(30)
Poland	I3B/P(37)
Germany, Austria	I3B/P(50)

5.2 Connecting the gas cylinder to the appliance

This appliance is only suitable for use with low-pressure butane or propane gas or LPG mixtures, fitted with the appropriate low-pressure regulator via a flexible hose. The hose should be secured to the regulator and the appliance with hose clips. This barbecue is set to operate at a 28 Mbar regulator with butane gas and a 37 Mbar regulator with propane gas, 30 Mbar for LPG mixtures or 50 Mbar for LPG mixtures. Use a suitable regulator certified to BSEN 16129. Please consult your LPG dealer for information regarding a suitable regulator for the gas cylinder.

1. Regulator and Hose

- These items are not supplied with the barbecue, but replacements are available from the retailer or an authorised LPG gas stockist. Use only regulators and hoses approved for LP Gas at the pressures mentioned above. The life expectancy of a regulator is estimated to be 10 years. We recommended you to change the regulator within 10 years of the manufactured date.
- The use of the wrong regulator or hose is dangerous. Always check that you have the correct items before operating the barbecue.
- The hose used must conform to the relevant standards for the country of use. The length of the hose must be max. 1.5 metres. Worn or damaged hose must be replaced. Ensure that the hose is not obstructed, kinked or in contact with any part of the barbecue other than at its connection.

2. Storage of Appliance

- Storage of an appliance indoors is only permissible if the cylinder is disconnected and removed from the appliance. When the appliance is not in use for a long period, it should be stored in its original packaging and a dry, dust free environment.
- Please clean the grill of remaining food and oil stains etc. after each use. Dry all components to avoid rust.
- When not in use, cover the grill with a protective cover to protect from rain and other substances that could cause rust or other damage. Always store indoors.

3. Gas Cylinder

- The gas cylinder should not be dropped or handled roughly. If the appliance is not in use, the cylinder must be disconnected. Replace the protective cap on the cylinder after disconnecting.
- Cylinders must be stored outdoors in an upright position