



Vivace Decorative (Glazed Porcelain)



Rice - RIC
NATVIVRIC44G
4"x4" Pressed Porcelain Field Tile - Gloss



Rice - RIC
NATVIVRIC49G
4"x9" Pressed Porcelain Field Tile - Gloss



Rice - RIC
NATVIVRIC918M
9"x18" Pressed Porcelain Field Tile - Matte



Fossil - FOS
NATVIVFOS44G
4"x4" Pressed Porcelain Field Tile - Gloss



Fossil - FOS
NATVIVFOS49G
4"x9" Pressed Porcelain Field Tile - Gloss



Fossil - FOS
NATVIVFOS918M
9"x18" Pressed Porcelain Field Tile - Matte



Atlantic - ATL
NATVIVATL44G
4"x4" Pressed Porcelain Field Tile - Gloss



Atlantic - ATL
NATVIVATL49G
4"x9" Pressed Porcelain Field Tile - Gloss



Atlantic - ATL
NATVIVATL918M
9"x18" Pressed Porcelain Field Tile - Matte



Caviar - CAV
NATVIVCAV44G
4"x4" Pressed Porcelain Field Tile - Gloss



Caviar - CAV
NATVIVCAV49G
4"x9" Pressed Porcelain Field Tile - Gloss



Caviar - CAV
NATVIVCAV918M
9"x18" Pressed Porcelain Field Tile - Matte



Motif Rice
NATVIVMOTRIC44G
4"x4" Pressed Porcelain Deco - Gloss



Incline Rice
NATVIVINCRIC44M
4"x4" Pressed Porcelain Deco - Matte



Roads Atlantic
NATVIVROAATL99M
9"x9" Pressed Porcelain Deco - Matte



Peak Caviar
NATVIVPEACAV99G
9"x9" Pressed Porcelain Deco - Gloss



Roads Caviar
NATVIVROACAV99M
9"x9" Pressed Porcelain Deco - Matte

SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		NATVIV...44G	4"x4"	Pressed Porcelain Field Tile - Gloss	40	5.38
		NATVIV...49G	4"x9"	Pressed Porcelain Field Tile - Gloss	20	5.38
		NATVIV...918M	9"x18"	Pressed Porcelain Field Tile - Matte	10	10.87
Deco		NATVIVMOTRIC44G	4"x4"	Pressed Porcelain Deco - Gloss (Motif Rice)	40	5.38
		NATVIVINCRIC44M	4"x4"	Pressed Porcelain Deco - Matte (Incline Rice)	40	5.38
		NATVIVPEACAV99G	9"x9"	Pressed Porcelain Deco - Gloss (Peak Caviar)	20	10.80
		NATVIVROACAV99M	9"x9"	Pressed Porcelain Deco - Matte (Roads Caviar)	20	10.80
		NATVIVROAATL99M	9"x9"	Pressed Porcelain Deco - Matte (Roads Atlantic)	20	10.80
Trim		∅ NATVIV...LNRG	1/2"x12"	Pencil Liner - Gloss	50	-

ANSI TECHNICAL SPECIFICATIONS - Gloss

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	N/A	3	Unaffected	6	ISO ≥ 600 N	≤ 0.5%	Unaffected

Shade Variation



V3-Moderate

ANSI TECHNICAL SPECIFICATIONS - Matte

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	4	Unaffected	7	ISO ≥ 600 N	≤ 0.5%	Unaffected



Made in Spain



Glazed Porcelain

APPLICATIONS - Gloss

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◻	◻		◻	◻
Commercial		◻	◻		◻	◻



Non-Rectified

APPLICATIONS - Matte

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●†	◻	◻	◻	●†	◻
Commercial	●†	◻	◻	◻	●†	◻



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- * Special Order only



† The TCNA does not rate products for exterior floors. Project specifier must determine product suitability for exterior floor applications by evaluating specific project conditions, type of use, traffic, drainage, expected contaminants (such as water, oil, grease, etc.), wear, maintenance, and manufacturer's specifications and guidelines. Use caution--product may not be suitable for pool decks. Not suitable for ramps. No polished tiles; only textured surfaces may be suitable.

The maximum allowable installation offset is 33%. Minimum grout joint must be 3/16 inch. Please refer to the most current TCNA Handbook. Use of a leveling system is strongly recommended.

For installation of all gloss, polished, polished glazed, lappato, and honed porcelain/ceramic tiles, use a grout release prior to grouting to prevent absorption of the grout into the tile's micropores. Use a grout color that matches the predominant color of the tile. Refer to grout manufacturer's specifications to ensure use of proper grout. Refer to tile manufacturer's specifications to determine if the polished or honed tile is appropriate for commercial applications. Tiles with a polished finish are not appropriate for wet or exterior floor applications. Do not use acidic cleaners.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

