

Item #

UPC Code:

Light Kit

K9525L-1

706411063404

Category Type:

Product Family Name:

Finish:


Category: LED

Certification 4000048 Patents:

Notes:



Image File Name: K9525L-1.jpg



MEASUREMENTS

Blade Finish:

Reversible

No

Blades:

Blade Material:

Slope: No

Blade Sweep:

No. of Blades: Blade Pitch:

Hanging Weight:

0" Downrod 1:

Downrod 1

Downrod 2:

2.73 Downrod 2

Outside Dia:

Outside Dia:

Ceiling to LowestCeiling to Blade Lead Wire:

Motor Size:

Point: (Dim A) (Dim B)

Low Low/Med. Medium Med/High High

RPM: Amps: **Watts:** CFM:

CFM/Watts:

LAMPING

No. of Bulbs: Light Type: Light Kit Optional: No

4W, LED

Socket: Max Bulb

E12, CANDELABRA Wattage:

Integrated Dimmable: Ballast: Uplight: Rated Life No

Light Kit: No No

Hours: 10000

Initial Delivered Color Temp.: CRI:

Bulb/LED Included: 3000 90 Lumens: Lumens: 900.0 856.5

Yes

GLASS

Description: Material: Frosted White **GLASS** Quantity: Part No.:

Height: Width: Length: 12.28 12.28 2.2



CONTROLS

Pull Chain Control: Works with Remote Yes

Control: No

Works with Wall

Included Remote Reversible:

Control:

No Included Wall Control:

No Control:

Compatible Remote Compatible Wall

Integrated Smart

Smart Control:

No

Control(s): Control(s):

Control:

Compatible Smart

Control:



SHIPPING

Carton Width: Carton Height: Carton Length:

14.13 14.13 6.38

Carton Weight: Carton Cubic Feet: Small Package Shippable:

4.18 0.737 Yes

Master Pack Width: Master Pack Height: Master Pack Length: 29.0 14.75 13.75

Master Pack Weight: Master Cubic Feet: Multi-Pack: Master Pack: 20.13 3.404 1

LED

LED

ETL

Intertek



WARNING: Handling this product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or

4



other reproductive harm. Wash hands with soap and water after installing, handling, cleaning or otherwise touching this product. For more information go to: www.P65Warnings.ca.gov.