




# LED LINKABLE UNDER-CABINET LIGHT

LEDUC12  
LEDUC21  
LEDUC24  
LEDUC33



INSTRUCTIONS PERTAINING TO RISK OF FIRE OR INJURY TO PERSONS  
READ ALL INSTRUCTIONS

## IMPORTANT SAFETY INSTRUCTIONS

SAVE THESE INSTRUCTIONS

**TOOLS AND MATERIALS REQUIRED:**

Phillips Screwdriver

Wire Cutters

Wiring supplies as required by electrical code

Pliers

Drill

### SAFETY PRECAUTIONS:



1. TURN OFF ELECTRICAL POWER BEFORE STARTING INSTALLATION OF LIGHT FIXTURE.
2. THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A CERTIFIED ELECTRICIAN FAMILIAR WITH LOCAL MUNICIPAL CODES AND REQUIREMENTS.
3. CAUTION-RISK OF ELECTRIC SHOCK. CONSULT A QUALIFIED ELECTRICIAN TO ENSURE CORRECT BRANCH CIRCUIT CONDUCTOR.

### PACKAGE CONTENTS

| PART | DESCRIPTION                      | QTY |
|------|----------------------------------|-----|
| A    | LED light                        | 1   |
| B    | Mounting screw for LEDUC12/21/24 | 2   |
|      | Mounting screw for LEDUC33/42    | 3   |

| PART | DESCRIPTION                     | QTY |
|------|---------------------------------|-----|
| C    | 1/4" Romex connector            | 1   |
| D    | Link cord (use with option #2)  | 1   |
| E    | Power cord (use with option #2) | 1   |

### OPTION #1: HARDWIRE





1. Determine the desired location for mounting the fixture, then measure the distance between the centers of the 2 keyholes on the back of the fixture. Mark the locations of the keyhole on the underside of the cabinet with a pencil. Drill pilot holes for the mounting screws with a small drill. To unscrew to remove the back metal cover off the fixture, tighten the mounting screws into the cabinet.

2. Knock blind knockout open on the side of the fixture and install the 1/4" Romex connector. Connect supply wires to wires on the fixture with wire nuts or push wires into quick connectors. Connect white to white, black to black, green or bare copper wire to green wire.

3. Complete the installation by returning the fixture cover with the screws. Also please make sure to let metal cover retainer in position of the notch to keep the cover close even (LEDUC33/LEDUC42).

### OPTION #2: PORTABLE



1. Determine the desired location for mounting the fixture, then measure the distance between the centers of the 2 keyholes on the back of the fixture. Mark the locations of the keyhole on the underside of the cabinet with a pencil. Drill pilot holes for the mounting screws with a small drill. Start tightening the mounting screws into the cabinet. Do not drive them completely.

2. Attach the fixture to the mounting screws. Turn fixture left or right to lock.

3. Complete the installation by plugging in the power cord.

Customer service: 888-945-5221

NOTE: 10 units maximum.

Do not return to the store.

Made in China