

# ALTAIR

SMART  
TOILET

## Specifications

|                        |                    |   |
|------------------------|--------------------|---|
| Rated voltage          |                    | 120V~   |
| Rated frequency        |                    | 60Hz  |
| Rated power            |                    | 1050W   |
| Water supply hose type |                    | DN15(G1/2")   |
| Water Inlet            | Minimum pressure   | 35psi, ensuring a flow of water at least 10.57gal/min |
|                        | Maximum pressure   | 108.8psi (static state)                               |
| Toilet                 | Flush type         | Tornado flush   |
|                        | Rough-in           | Rough-in 12in   |
| Washing                | Heating type       | Instant heating                                       |
|                        | Temp of warm water | OFF/93.2°F-102.2°F (4 levels)                         |
|                        | Safety system      | Butterfly thermostat, thermal fuse, flow sensor       |
| Dryer                  | Dryer temp range   | OFF/ 95°F-131°F (4 levels)                            |
|                        | Dryer air speed    | > 4m/s  |
|                        | Safety system      | Thermal fuse, bi-metal                                |
| Heated seat            | Heat temp range    | OFF/93.2°F-102.2°F (4 levels)                         |
|                        | Safety system      | Thermal fuse  |

## SM5002-WH

Wall

Unit: inches

