



ASSEMBLY INSTRUCTIONS

- 1, Carefully unpack and identify each part to make sure you have everything ready for installation. Lay out each part on a clean flat area such as a table or the floor.
- 2, Shut down the main electrical supply from the fuse box or circuit breaker in your house or building.
- 3, Screw off Cap Nut and take off the mounting bracket.
- 4, Fasten the mounting bracket onto the outlet box using the 2 outlet box screws (short).
- 5, Connect the wires from the fixture to the power supply wires from the outlet box and cover with the wire connector.
 - A, Twist together the neutral wire from the fixture with the neutral wire from the outlet box. Cover with the wire connector.
 - B, Twist together the live wire from the fixture with the live wire from the outlet box. Cover with the wire connector.
 - C, Loop the bare copper ground wire from the fixture body under the head of the green screw on the mounting bracket, then connect it with the green ground wire from the fixture to the ground conductor from the supply circuit and cover with the wire connector.
- 6, Carefully position all wirings inside the outlet box.
- 7, Place the canopy assembly over the outlet box, allow the heads of the support screws (long) to go through the holes of the canopy, then secure by tightening the Flat Screw Nut.
- 8, Carefully position the glass shade to the lamp holder with a metal ring.
- 9, Install the bulb (not included) to the socket on the fixture body. Use E26*1 60W.
- 10, Turn on the electrical power in your house or building to test the lamp. Save these instructions for future use.

Cleaning

- Use only a soft cloth to dust and clean your new lamp.
- Do not use any chemicals, polishes or abrasives.

Warning: Do not immerse your lamp in water; doing so will damage the wiring.