

# **RAVEN ROCK BRUSHED**

engineered





## **RAVEN ROCK BRUSHED**



Style Number	220SA		
Construction	Epic Plus		
Thickness	1/2" (11.93mm)		
Width	4.94"		
Species	Hickory		
Texture	Wire Brushed		
Gloss Level	7%		
Janka Hardness Rating	1787		
Edge Description	Microbeveled		
End Description	Microbeveled		
SF per carton	15.80		
SF per pallet	948.00		
Installations	Nail, Staple, Glue, Float		
All measurements are nominal	Cartons may include random lengths		

#### **Features**

- · Rich hickory character showcased in traditional & contemporary color palette
- Also available in smooth version 219SA Raven Rock Smooth

### **Sundry Recommendations**

Style #	Style Name	Coverage	Moisture Test		
ADHESIVES					
HS105	35MC — Urethane	35 SF / gal for moisture	No Moisture test required	Sound control & crack suppressant	
		60 SF / gal as adhesive	Up to 5 lbs. or 85% RH		
111SA	3-in-1 Ultra — MS	35 SF / gal for moisture	No Moisture test required	Sound control & crack suppressant	
		70 SF / gal as adhesive	Up to 5 lbs. or 85% RH		
HS304	DMC140 — Urethane	35 SF / gal for moisture	No Moisture test required		
SWADH	UreBond Plus	35 SF / gal for moisture	Up to 8 lbs. or 85% RH		
		60 SF / gal	Up to 5 lbs. or 85% RH		

**Trim Pieces** length: 78" (\*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking — but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)







\*Overlap Reducer



SSH12 Flush Stairnose



**SOSH2**\*Overlap
Stairnose



SCH12 Threshold | Carpet Reducer



TMH78 T-Molding



**QTR96** Quarter Round

#### **Benefits**

















