

WAC LIGHTING

Balto I

Flush Mount 4CCT

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
FMW703605 5"	2700K/3000K/3500K/4000K	BK Black WT White	13.2W	1125	599

Example: **FMW703605S-WT**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Minimalist design meets maximum versatility. Defined by its clean circular profile and frosted ringed diffuser, BALTO I blends sophistication with modern architecture. Built to endure the elements, this versatile fixture is wet rated for outdoor use.

FEATURES


- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option available for sauna application. Durable and heat resistant. Available in 3000K only (Model#FMW703605S)
- Sauna application operating temperature: Min -4 F/Max 185 F
- Weather resistant powder coated finishes
- ACLED driverless technology
- 5 year warranty




SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K,3000K
Input:	120V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Wet Location Listed
Construction	Aluminum body with interior frosted PC diffuser

FINISHES:



LINE DRAWING



FMW703605

WAC LIGHTING

Balto I

Flush Mount 4CCT

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
FMW703605S 5"	3000K	BK Black WT White	3.3W	373	128

Example: **FMW703605S-WT**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Minimalist design meets maximum versatility. Defined by its clean circular profile and frosted ringed diffuser, BALTO I blends sophistication with modern architecture. Built to endure the elements, this versatile fixture is wet rated for outdoor use.

FEATURES


- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option available for sauna application. Durable and heat resistant. Available in 3000K only (Model#FMW703605S)
- Sauna application operating temperature: Min -4 F/Max 185 F
- Weather resistant powder coated finishes
- ACLED driverless technology
- 5 year warranty



SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K,3000K
Input:	120V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Wet Location Listed
Construction	Aluminum body with interior frosted PC diffuser

FINISHES:



REPLACEMENT PARTS

RPL-DIF-703605 - BALTO I REPL DIFFUSER