

Outdoor Shower Co., LLC

Dallas, Georgia

www.outdoorshowerco.com—1-866-shower1

Manufacturers of Quality Stainless Steel Showers



WMHC-445-SS - Wall Mount Stainless Steel Hot & Cold

WMHC-445-SS PARTS LIST:

- | | | |
|---|-----------|---|
| ① | GL150-6-S | 6" Stainless Steel Raincan Shower Head—Satin Finish |
| ② | SR-41-90 | ½" 90 degree Stainless Steel Riser |
| ③ | WB-2.5 | 2 ½" Stainless Steel Wall Bracket (Complete with 2 stainless steel screws and set screw |
| ④ | HC-445-SS | Hot & Cold Stainless Steel Valve - 8" Center—ADA Compliant Lever Handles |

Accessories may vary due to availability and slight modifications by the manufacturer.



Installation Guidelines

Recommended Shower Head Height: 78"
Water Supply Lines should be roughed in at approximately 40" from flooring surface with 8 inch spread.

- Install 1/2" water line with 8" spread, exposed 1" through mounting surface.
- Place trim flanges over exposed 1/2" water line pipes.
- Secure supply arms to piping. Position them as close as possible to desired location to mount faucet.
- Flush lines.
- Assemble Mounting Bracket and slide over Riser. Tighten set screw when at a desired position.
- Attach unit to wall with stainless steel screws by marking position using wall bracket as a guide.
- Attach Shower Head to Riser. Teflon Tape is not needed.

NOTE: In some states a check valve may be required inside the wall for the hot & cold water supply lines. This part is not provided by Outdoor Shower Co., but is available through a plumbing contractor or wholesaler.

