





specifications:

1. Visible surface must be smooth and smooth, natural transition.
2. Against the wall must be vertical, the other several faces also try to vertical.
3. Make sure there is no water in the basin.
4. Can Not have acute angle, visible surface of the corner is R=2.
5. Positive and negative tolerance:2mm

				Size:1800*500*50mm		
Mark	Initial release	Change content	Signature date	Qty	Unit	Proportion
Design		standardization		1	PCS	1
Revise		Check				
Technology		Approve		Total	1 PCS	No. 1 PCS

PHA.5  
PHA  
HAT  
DIM  
HID.5  
HID  
CEN.5  
CEN  
DRW2  
DRW



### BASIN DIMENSIONS (inch)

Sink Size	Length (from left to right)	Width (from front to back)	Depth (from top to bottom)	Distance between the side of the <b>faucet hole</b> and the <b>back edge of the basin</b>	Distance between the center of the <b>faucet hole</b> and the <b>back edge of the top</b>	Distance between the center of the <b>drain hole</b> and the <b>back edge of the top</b>	Distance between the <b>center of the faucet/drain hole</b> and <b>closer side edge of the top</b>	Distance between <b>two faucet/drain holes</b> (center to center)	Distance between the <b>two basins</b>
									
<b>24" SINK</b>	18	12	4	1.75	2.35	10.5	12	/	/
<b>30" SINK</b>	18	12	4	1.75	2.35	10.5	15	/	/
<b>36" SINK</b>	18	12	4	1.75	2.35	10.5	17.75	/	/
<b>42" SINK</b>	20	12	4	1.75	2.35	10.5	21	/	/
<b>48" SINK</b>	20	12	4	1.75	2.35	10.5	23.5	/	/
<b>60"S SINK</b>	24	13	5	1.75	2.5	9.25	29.5	/	/
<b>60"SL SINK</b>	20	12	4	1.75	2.35	10.5	14.75	/	/
<b>60"SR SINK</b>	20	12	4	1.75	2.35	10.5	14.75	/	/
<b>60"D SINK</b>	18	12	4	1.75	2.35	10.5	14.75	29.5	11.5
<b>72"D SINK</b>	20	12	4	1.75	2.35	10.5	17.75	35.5	15.75
<b>84"D SINK</b>	20	12	4	1.75	2.35	10.5	21	41.75	22

Faucet Hole:  $\phi$  1.2

Drain Hole:  $\phi$  1.75