

# Pull Handles


## Square Series



66 6520 ■

Handle cross-section □ 25 × 25 mm  
 Safety clearance S = 46 mm  
 Fastening M8

Standard length 500 mm  
 (also available in special lengths, please see order form page 17)




All details subject to modification

### Fastening Methods (Details on page 73)

- A** Back-to-Back
- B** Through-Bolted
- C** Concealed - Threaded Insert
- D** Concealed - Drop Clamp

# Order Form

## Pull Handles 6519, 6520 and 6548



Please use a copy of this page to order the door handle series 6519, 6520 and 6548 in variable lengths.

Start by using the product numbers to define the desired version.

In the table below, please enter the quantity and overall length. Then add the distance(s) (A) between the support(s) and the end support distance (R).

66 6519 99 ( 25 × 25 mm)



66 6520 99 ( 25 × 25 mm)



To ensure stability, the support distance (A) should not exceed 1200 mm.

66 6548 99 (40 × 10 mm)



To ensure stability, the support distance (A) should not exceed 600 mm.

All details subject to modification

Quantity	Overall length	Support distance			End support distance*		Fastening type
	L	A <sub>1</sub>	A <sub>2</sub>	A <sub>3</sub>	R <sub>1</sub>	R <sub>2</sub>	

\* min. 30 mm, max. 350 mm for 6519, 6520

\* min. 30 mm, max. 250 mm for 6548