

## **CHANDELIER FIXTURE** **INSTALLATION INSTRUCTIONS**

Please read carefully and save these instructions, as you may need them at a later date.

### **CAUTION**

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

### **GENERAL**

All electrical connections must be in accordance with local and National Electrical Code (N.E.C) standards. If you are unfamiliar with proper electrical wiring connections, obtain the services of a qualified electrician. Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

### **ASSEMBLY AND INSTALLATION**

- 1, Screw the LOOP to the fixtures.
- 2, Attach the Cross Bar to the Outlet Box by using 2 pcs Mounting Screws upwards. Screw the NIPPLE with the WASHER and HEX NUT-1 to the CROSS BAR.

Make wire connections:

- Smooth wire (w/markings) from the light to black wire from power source.
  - Ribbed wire (w/o markings) from the light to white wire from power source
  - Attach the ground wire to the cross bar with a green ground screw.
- Carefully tuck wire back into the OUTLET BOX

- 3, Screw the TOP LOOP to the NIPPLE, Place the CANOPY against the OUTLET BOX, and secure it with the TOP NUT.

- 4, Attach the SHADE to the fixture, screw with the RING.

- 5, Install bulbs. (Please do not exceed the maximum capacity which is recommended on the sockets).

INSTALLATION IS NOW COMPLETED.

