

Project:

Spec Sheet

Description: Surface-mounted lights are neatly compact and solidly built. They offer a range of lens variations within the tightly defined geometry of their die-cast rings. Also available as a [Downlight Sconce](#), [Up/Down Sconce](#), [Bollard](#), and [Double Bollard](#).



Type #:

Dimensions

Height: 2.5"
Diameter: 5"
Canopy/Backplate/Base: 5"

Electrical Specs

Bulb(s) Included?: Yes
Bulb 1 Type: Integral LED
Bulb Quantity: 1
Input Voltage: 120VAC
Wattage: 10
Initial Lumens: 1040
Color Temperature: 3000K
CRI: 90
Power Supply Type: Driver
Power Supply Quantity: 1
Power Supply Location: Outlet Box
Dimming Type: TRIAC/ELV
Bulb Max Wattage: 10

Installation

Installation: Licensed electrician required

Shipping

Carton 1 L x W x H: 9" X 9" X 6"
Carton 1 Gross Weight: 3 LBS
Fixture Weight: 2

Shade

Lens Type: Clear Cylinder Lens
Shade 1 Material: Clear Polycarbonate

Available Finishes

Available Finishes: Textured Bronze (.72), Textured Gray (.74), Textured White (.98)

General Listings

Features: Wet Rated
Certification: cETL
Color/Finish: Textured White (.98)
Dark Sky Friendly: N