



## General Information

|                 |                                   |
|-----------------|-----------------------------------|
| Type            | wall / ceiling light              |
| Product segment | Indoor                            |
| Theme           | sonstige / nicht zuordenbar       |
| FSC®            | FSC® Mix70% Hevea br FSC® C152762 |

## Dimensions

|                            |               |
|----------------------------|---------------|
| Article Height (in mm)     | 60            |
| Article Length (in mm)     | 460           |
| Net Weight (in kg)         | 1.08 Kilogram |
| Article Overhang (in mm)   | 120           |
| Article Width (in mm)      | 140           |
| Article Diameter (in mm)   | 380           |
| Canopy Length (in mm)      | 530           |
| Canopy Width (in mm)       | 45            |
| Canopy Height (in mm)      | 25            |
| Base Diameter (in mm)      | 645           |
| Base Length (in mm)        | 230           |
| Base Width (in mm)         | 150           |
| Installation Depth (in mm) | 26            |
| Cutout (in mm)             | 205           |
| Canopy Diameter (in mm)    | 460           |

## Material & Colour

|                      |                          |
|----------------------|--------------------------|
| Enclosure Material   | steel                    |
| Enclosure Colour     | black                    |
| Glass/Shade Material | plastic, brilliant glass |
| Glass/Shade Colour   | black, clear             |
| Cable Colour         | black                    |

## Functionality

|                             |                     |
|-----------------------------|---------------------|
| Switch Type                 | without switch      |
| Battery                     | No                  |
| Function                    | LED not replaceable |
| Battery Type                | CR2032              |
| Sensor Angle (in °)         | 120                 |
| Sensitivity min. (in lux)   | 30                  |
| Burning Time min. (in sec.) | 5                   |
| Burning Time max. (in sec.) | 15                  |
| Distance (in Meter)         | 6                   |

## Technical Information

|                   |                  |
|-------------------|------------------|
| Protection Degree | IP20             |
| Protection Class  | 2                |
| Mains Voltage     | 220-240V,50/60Hz |
| Operation Voltage | 24V              |
| max. Wattage (1)  | 3X3,5W           |
| Dimmable          | No               |
| Spannung          | 220-240V 50/60Hz |
| U out             | 46-70V           |
| I out             | 300mA            |
| Hz                | 100Hz            |

## Illuminant 1

|                      |           |
|----------------------|-----------|
| Illuminant Type (1)  | E27       |
| Illuminant incl. (1) | Exclusive |
| Socket Type (1)      | E27       |

## Illuminant 1

|  |   |
|--|---|
| Socket Type (1)                        | LED   |
| Illuminant Type (1)                    | LED   |
| Illuminant incl. (1)                   | Inclusive                                     |
| Kelvin Complete                        | 3000K   |
| Light colour Complete                  | WARM WHITE                                    |
| Nominal Lifetime (in h)                | 25000   |
| Switching Cycles                       | 15000   |
| Energy efficiency class (EEI)          | F   |
| Dimmable                               | No  |
| Info changeability□light source/driver | LED + driver can be exchanged by a specialist |
| Rated Lamp Power (0,1W precision)      | 36  |
| Colour Tolerance (LED, SDCM)           | <6  |
| Lumen Complete                         | 1200  |

## Illuminant 1

|  |   |
|--|---|
| Socket Type (1)                        | GU10  |
| Illuminant Type (1)                    | GU10-LED  |
| Illuminant incl. (1)                   | Inclusive   |
| Energy efficiency class (EEI)          | F   |
| Info changeability□light source/driver | LED exchangeable by customers, no driver included |

