



WMCL Wall Mount Cylinders, 4" and 6"

36 Configurations, One Lighting Solution

Lithonia Lighting® WMCL Wall Mount Cylinders seamlessly blend style and function, offering 36 configurations in one SKU for customizable, effortless illumination.

Available in two sizes—WMCL4 (2,400 lumens) and WMCL6 (4,700 lumens)—these cylinders provide optimal lighting for residential and commercial projects alike. Built-in switches allow you to choose light direction—up, down, or both, color temperature and an on/off photocell, giving you full control. Luminaire is rated IP66 to ensure longevity even during harsh conditions.

Designed for walkways, entryways, or general illumination, WMCL Wall Mount Cylinders deliver a tailored, professional wall mount lighting solution.

Features & Benefits:

- Easily adjust lighting direction with a built-in switch to choose Up, Down, or Both
- Switchable CCT of 3000K, 4000K and 5000K for adaptable lighting
- Available in 45° and 75° beam angles to suit various applications
- Integrated dusk-to-dawn functionality with a built-in photocell for automatic operation
- Optional emergency battery backup for reliable illumination during power outages



WMCL Wall Mount Cylinders, 4" and 6"

Switchable Features for Customizable Illumination

With Lithonia Lighting® Wall Mount Cylinders, you can effortlessly customize your lighting to suit any space. The switchable options for color temperature, lighting direction, and photocell functionality make it easy to adapt to any application, ensuring the perfect light for every environment.



Catalog Number	Size	Wattage	Lumens @50K	LPW	Beam Spread	Color	CCT	Voltage	Photocell	Emergency Battery	CI Code	Lead Time
WMCL4 P1 SWW2 A45 UVOLT PE DDBXD M4	4"	19	2,479	130	45°	Dark Bronze	30K 40K 50K	UVOLT	On/Off	No	2877PY	Stock
WMCL6 P1 SWW2 A45 UVOLT PE DDBXD M4	6"	31	4,728	153	45°	Dark Bronze	30K 40K 50K	UVOLT	On/Off	No	2877R1	Stock
WMCL4 P1 SWW2 A75 UVOLT PE DDBXD M4	4"	19	2,433	128	75°	Dark Bronze	30K 40K 50K	UVOLT	On/Off	No	2903FT	Stock
WMCL6 P1 SWW2 A75 UVOLT PE DDBXD M4	6"	31	4,520	146	75°	Dark Bronze	30K 40K 50K	UVOLT	On/Off	No	2903FU	Stock
WMCL4 P1 SWW2 A75 MVOLT PE E4WC DDBXD M4	4"	19	2,479	130	75°	Dark Bronze	30K 40K 50K	MVOLT	On/Off	Yes	291271	10 Days
WMCL6 P1 SWW2 A75 MVOLT PE E4WC DDBXD M4	6"	31	4,520	146	75°	Dark Bronze	30K 40K 50K	MVOLT	On/Off	Yes	291273	10 Days
WMCL4 P1 SWW2 A45 MVOLT PE E4WC DDBXD M4	4"	19	2,433	128	45°	Dark Bronze	30K 40K 50K	MVOLT	On/Off	Yes	291277	10 Days
WMCL6 P1 SWW2 A45 MVOLT PE E4WC DDBXD M4	6"	31	4,728	153	45°	Dark Bronze	30K 40K 50K	MVOLT	On/Off	Yes	29127G	10 Days