



Cushion Assembly Instructions

Insert Foam Into Cushion Covers

1 Open the Vacuum Package



- Carefully cut open the plastic bag using scissors.
- ⚠ **DO NOT** cut too deep to avoid damaging the foam.
- The foam will start expanding immediately.



Helpful Tip: Insert the foam right after opening while it is still compressed. This **makes installation easier!**

2 Insert Foam Immediately

A Seat Cushion

- Insert the foam into the seat cushion cover.
- The square foam piece includes **extra thickness at the front** make sure this part is positioned **toward the front edge** of the seat.
- It is normal that the fit feels tight.
- This ensures a full, premium look once installed.



B Back Cushion

- Insert the **cushion insert** into the **backrest** cover first.
- Then add the **2 layers of foam sheets** inside cushion (labeled A/B) inside the cushion.
- It is normal that it feels tight when you close the zipper.
- **It is recommended that there are 2 people ideally to do this.**



This will:

- ✓ Improve comfort
- ✓ Provide better support
- ✓ Give a fuller shape to the back cushion

1 Insert Cushion Insert FIRST



2 Add 2 Foam Sheets (A + B)



3 Adjust & Close

- Adjust the foam to fill all corners evenly.
- Smooth and shape the cushion by hand.
- Close the zipper completely.



Please allow 24 hours for the cushions to fully expand.

