



2\*E26 Max 40W Not included

# Double Wall Sconce Instruction

## Safety Warning

Turn OFF power at the breaker panel and verify the wires are not live before beginning.

---

## Installation Steps

- **Step 1: Attach the Mounting Plate**

Attach the round mounting plate to the wall junction box with the two #8-32 screws supplied. The two threaded posts must face outward and sit level.

- **Step 2: Wire the Fixture**

Wire the fixture body:

1. Connect black (hot) to black, white (neutral) to white, and green/bare (ground) to green/bare or the ground screw on the plate.
2. Twist connectors clockwise and tuck all splices neatly inside the box.

- **Step 3: Mount the Fixture Body**

Place the fixture body onto the mounting plate, aligning it with the threaded posts, and press firmly against the wall.

- **Step 4: Tighten the Locking Screw**

Secure the fixture by tightening the vertical screw until the fixture body is firmly attached to the mounting plate.

- **Step 5: Install the E26 Bulbs**

Install two E26 bulbs (max 40W each, not included) by screwing them clockwise into the sockets until secure.

- **Step 6: Position the Glass Shades**

Carefully slide the cylindrical glass shades over both sockets, ensuring they are properly aligned with the fixture housings.

- **Step 7: Secure the Shades with Retaining Rings**

Secure the glass shades by tightening the retaining rings onto each socket. Hand-tighten only to avoid cracking the glass.

---

## Final Check

Restore power at the breaker panel and test the sconce. Both bulbs should illuminate evenly and the glass shades should be secure with no wobble.