



### Installation steps:

- 1-2. insert the lamp arm into the hole of the lamp body
- 3-4. lock the lamp arm with screws and nuts
5. Buckle the chain into the lifting ring, and then tighten the movable buckle
6. Fix the hanging board on the junction box with the screws on the accessory package
7. Connect the lamp cap line with the line of the same color as the main line with a terminal cap (connect a lead to the second layer)
8. Align the hole on the lamp arm with the hole on the element
9. lock the lamp arm with screws and nuts
10. Put the installed lamp arm cover at a, and then tighten it with iron parts (connected with the first layer)
11. Tighten the boom
12. Tighten Part B to the boom
13. Insert light arm into the side bore of Part B
14. Tighten the lamp arm with the nut gasket
15. Connect the lamp cap line with the line of the same color as the main line with a terminal cap
16. Close the lid
17. Tighten the nut
18. Connect the main line of the lamp body with the wires reserved on the ceiling with wiring caps
19. Cover the junction box with a top plate
20. Tighten the ring
21. Twist the bulb to the lamp holder

### Attention:

1. Please cut off the power supply before installation to prevent electric shock (installation by certified electrician is recommended)
2. Due to the different display, the actual color can be different from the image
3. Due to the manual measurement of lamp body size, there may be a deviation of 1 / 2 inch
4. If you have any questions or lost parts, please feel free to contact us and we will try our best to help you