

Door Awning

5934C Series W59"xD34"/W1500xD870mm

Assembly Instruction

Only for masonry house



























Wooden











Ladder

Electric Hammer Electric Screw 1/8",7/32",31/64" Driver

Driller Bits

Protection Goggles

Cross Screwdriver

Spanner

Safety Advice & Cleaning

Advices on Safety before assembly


- Make sure there are no hidden pipes or cables in the wall before drilling.
- Please strictly follow the steps listed in the instruction manual.
- Sort the parts and check according to the part list & exploded drawing.
- At least 2 persons are needed to assemble the awning.
- Do not attempt to assemble the awning in windy, snowing or rainy conditions.
- Always wear shoes, gloves, helmet and safety goggles.
- Dispose of all plastic bags safely keep them out of reach of children and pets.
- Keep children and pets away from the assembly zone.
- Do not attempt to assemble the awning if you are tired, have taken drugs, medicine or alcohol, or if you are prone to dizzy.
- When using a stepladder or power tools, ensure that you follow the manufacturers safety advice.
- Please consult your local official if any permits are required to install the awning.

Cleaning

- If your awning need cleaning, clean all falling things, like leaves, branches, dust, etc with a soft brush.
- Use a kind of mild detergent solution and rinse with cold clean water.
- Do not use corrosive, acetone, abrasive cleaners or other special detergent to clean the roof panel.
- Do not use high-pressure water gun to rinse the roof and Aluminum profiles directly.

Note:


You are solely reponsible for determining whether handling, storage, assembly, installation or use of this product is safe and appropriate in any location or for any given application. We are not responsible for any damages or injury to you, any other person or any property resulting from the improper handling, storage, installation, assembly or use of this product, or the failure to follow written instructions. Contact your retailer if any question in time.




PART LIST

5934C series									
PART No.	PART NAME	SECTION FIG.	QTY	SIZE	PART No.	PART NAME	SECTION FIG.	QTY	SIZE
1	Front/Back Beam		2	L150cm/L59"	10	Cross Flat Head Screw		4	UNC1/4"xW1/2" x L3/4"
2	Cap of Front/Back Beam		4	D2/5"x25/64"	11	Middle Beam		1	L150cm/L59"
3	Rubber Sealing Strip		4	L150cm/L59"	1 1/	Left Supporing Bracket		1	L78cm/L31"
4	Roof Panel		2	59"x32- 1/2"x0.135"	≺	Right Supporing Bracket		1	L78cm/L31"
5	Large Flat Head Screw		1 /1	UNC1/4"x D3/4"x L3/4"	14	Fabric Valance		1	L58"xW6"
6	Big Rubber Sealing Washer		1 /1	D1/4"xD45/64" xT5/64"	15	Masonry Screw		6	UNC5/16"x 3-1/2"
7	Rubber Sealing Washer		12	D1/4"xD25/64" xT1/24"	16	Screw End Cap		6	D3/4"x3/4"
8	Cap Nut		8	UNC1/4"	17	Steel Washer		8	D1/4"xD25/64" xT1/16"
9	Self-tapping Screw		6	UNC1/8"x1/4"					

Step 1: Roof Kit Assembly



① Please note the roof panel is film coated on both surfaces. The surface printed specification information **MUST** be toward sun when installation. ② Tear off two side films before installation. Mark the surfaces "up" or "down" with a mark pen for identification. polycarbonete sheet x 2pcs UPF80+ PC Toward UPF80+ Sun Toward Tear off Sun





Step 1: Roof Kit Assembly


into rubber strip #3 and panel #4 kit.

Parts standby No.11x 1 pc Middle Beam 7 Ensure the top of rubber strip is against the inside of middle beam. Use wooden hammer if needed. ⑤ Cap the part #11 middle beam **(6)** Make sure the edges of rubber strip is inside of

middle beam.










Step 1: Roof Kit Assembly











Step 1: Roof Kit Assembly


Parts standby




No.3x 2 pcs Rubber Sealing Strip



(13) Install the other 2 pieces of rubber sealing stri onto the outer edges of panels.





Step 1: Roof Kit Assembly





Parts standby



No.9x 6 pcs Self-tapping Screw


- (15) Drill through the sealing strip #3 & roof panel #4 from up to bottom along with the holes predrilled on front/back beam with a 1/8" dill bit one by one. Total 6 pieces holes.
- (16) Then screw the 3 materials, #1,#3 together with the self-tapping screws #9 provided in the hardware bag. Total 6 pieces screws.














Step 2: Supporting Bracket Installation









④ Drill the 6 installation (3 holes for each bracket) holes on marked positions with electric hammer equipped diameter 31/64 inch drill bit about 4 inch deep.

Step 2: Supporting Bracket Installation




(6) Insert and knock all of the 6 bolts #15 into drilled holes one by one, then tighten them in clockwise.






Pull the brackets downward hard to check whether they're fixed securely or not.


If they are not secure enough, the bolts might be not tightened enough. You need check and tighten them.



® Cap all bolts with the plastic bolt caps #16 included in hardware bag if the 2 brackets are secure.

Step 3: Roof Panel Kit Installation






How does the glue work?


• The glue is a gift, not a part of product.


В

- The glue is able to ensure the roof screws avoiding loosening after years of using, against wind and snow.
- It's not a necessory step to drip the glue, but it'll be better if used it.

Door









B: Pull up the cross flat screw # 10 & sealing washer #7.

7/16"

glue

Drip 1 drop of glue into each hole on middle beam, then tighten screws.






Insert the valance into the front beam of awning if you like it.

② Cap 4 end caps of front/back beams on each top.

Well done! Congratulation!





You've completed all steps of installation. Great Job!