

CHANDELIER FIXTURE INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them a later date.

CAUTION

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

Installation steps:

1. Screw the Loop into nipple, attach the arm onto the banding, then screw with the ball nut-2 and ball nut-3.
2. Thread the Nipple-1 to the Cross Bar, and tighten with the Washer and the Hex Nut. Attach the Cross Bar to the Outlet Box by using 2 pcs Mounting Screws upwards.
3. Choose a certain length of the Chain you need, and weave the Fixture Wire and the Ground Wire through the chain links. Spread one end link of chain to clamp securely to the Loop.
4. Thread the Fixture Wire and Ground Wire through the Top nut, Collar Loop, Canopy, Nipple-1 and Cross Bar in order.
5. Secure the Collar Loop to the Nipple-1 and then clamp the other end of the chain link to the Collar Loop.
6. Make wire connections:
 - Smooth wire (w/markings) from the light to black wire from power source.
 - Ribbed wire (w/o markings) from the light to white wire from power source
 - Attach the ground wire to the cross bar with a green ground screw.Carefully tuck wire back into the outlet box.
7. Attach the Canopy to the Cross Bar by inserting the Collar Loop, and then tighten with the Top Nut.
8. Thread the Nipple-2 into the coupling with Hex Nut-1, attached the tube-3, cover-4 and cover-5, then screw with the hex nut.
9. Put the Glass-7 into the Nipple-2, attached the plastic washer-8 and metal washer-9, then screw with the Hex nut-10.
10. Attached the Cover-11, then screw with the Finial-12.

Install bulbs. (Please do not exceed the maximum capacity which is recommended on the sockets).

