

Project: _____

Fixture Type: _____

Location: _____

Contact: _____

LED

Wall mounted • Damp location listed



Description:

This light features a thin, acrylic lens that provides even illumination. This specially designed 24in. linear bath fixture delivers ambient light to surfaces free of shadows. This is a perfect addition to modern applications. An integrated LED source provides energy and cost savings benefits. Can be installed vertically or horizontally.

Specifications:

- Brushed Nickel (plated)
- Aluminum Construction
- White Acrylic diffuser
- The white acrylic shade provides even illumination
- Square end caps and back plate are finished in Brushed Nickel
- The LED light is diffused to create an even glow
- Ideal for residential, commercial and multi-family applications
- Mount horizontally or vertically on the wall in bath and vanity settings
- Measures 24in W x 4-3/4in ht.
- 23w integrated LED, 1,600 delivered lumens 70 lumens/watt, 3000K color temperature, 90+ CRI.
- ETL Safety listed for use in damp locations
- Compatible with many ELV dimmers
- Our products are designed for exceptional quality, reliability, and functionality
- Includes installation instructions and mounting hardware
- Coordinating fixtures available
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- 6" of wire supplied
- Complies with "Americans with Disabilities Act" - ADA
- ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

Performance:

| | |
|------------------------|------------------------------------|
| Number of Modules | 1 |
| Input Power | 23w |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW (Source) | |
| Lumens/LPW (Delivered) | 1600/70 (LM-79) |
| CCT | 3000 K |
| CRI | 90 CRI |
| Life (hours) | 50,000 (L70/TM-21) |
| FCC | FCC Title 47, Part 15, Class B |
| Min. Start Temp | -30 °C |
| Max. Operating Temp | 30°C |
| Warranty | 5-year limited warranty |
| Labels | cETLus Damp location listed |
| | ENERGY STAR® qualified |
| | Meets California Title 24 JA8-2016 |

Images:



Dimensions:

Width: 24"
Depth: 3-1/2"
Height: 4-3/4"
H/CTR: 2-3/8" (horizontal)

Glass
Width: 23-1/8"
Height: 3"



Dimming Notes:

is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron NTELV-300

Lutron DVELV-300P

Lutron Caseta

Leviton 6681

Lutron AYCL-153P

Lutron MAELV-600

Lutron AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.