



Barn Door Hardware Kit (Basic)

- Easy to install
- Save space
- Fashionable appearance



Surface treatment: Frosted Black

Main materials: High Quality Steel

Product Bearing: Maximum 150 kg

Door thickness: 13/16" - 1-9/16"

NAME	PICTURE	EXPLAIN	SPECIFICATIONS						
			6FT SGL	6 FT SGL	6 FT DBL	8.2ft SGL	8.2ft DBL	10ft DBL	11.6ft DBL
ROLLER		Single door with 2 pulley screw for 40-45mm thick door	2	2	4	2	4	4	4
RAILS		Orbital length at least door Twice the width	4	4	4	5	5	6	7
Rail Spacers		When using hollow wall, please drill hole. Select the appropriate screw according to the bolt.	5	5	5	6	6	7	8
Installation screw		Need to increase the distance between door panels and walls. Replace the long screw.	5	5	5	6	6	7	8
			4	4	8	4	8	8	8
Door Stoppers		Installed at both ends of the track to restrict doors. The distance and action of left and right movement.	2	2	4	2	4	4	4
Anti Jumpers		It is installed between the track and the top of the door to prevent the door from popping out from the top during the moving process.	2	2	4	2	4	4	4
Floor Guide		Install on the floor to prevent the door from swinging back and forth. Doors need to be grooved at the bottom (width 07-1 cm and height 2 cm)	1	1	2	1	2	2	2
Installation tools		With the whole set of hardware to send and install a gadget. Random color and style	1	1	1	1	1	1	1

