

Color Temp & CRI	Lumens	Finish	Emergency Backup Battery
2700K/3000K/3500K /4000K/5000K	1080	BN Brushed Nickel	Emergency Backup
	1815 2410	BN Brushed Nickel BN Brushed Nickel	

DESCRIPTION

Multiple high-powered LEDs illuminate the acrylic diffuser uniformly without socket shadows which are common in conventional.

FEATURES

- 5-CCT Switchable between 2700K and 5000K
- Multiple LED array for uniform illumination
- Emergency Battery Backup in case of loss of power
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

- Construction:** Extruded aluminum with Acrylic Diffuser
- Power:** 15W, 25W, 31W
- Input:** 120-277 VAC, 50/60Hz
- Dimming:** TRIAC: 100-5%, ELV: 100-10%
- Light Source:** Integrated LED
- Lens:** Translucent acrylic diffuser
- Rated Life:** 50000 Hours
- Mounting:** Installs over a 3" or 4" junction box, Can be mounted on ceiling or wall in all orientations
- Finish:** Electroplated Brushed Nickel
- Operating Temp:** -4°F to 104°F (-20°C to 40°C)
- Standards:** ETL, cETL, Damp Location Listed, Energy Star 2.0, Title 24 JA8-2016 Compliant



FINISHES



Brushed Nickel

LINE DRAWING

