

It is a minimalistic fan design with an integral LED light kit and pull chain control of 3 fan speeds and 3 CCTs. Available in two sizes and multiple popular finishes, the fan is powered by a whisper-silent AC motor. Ideal for indoor rooms up to 10' x 10' for the 44" model, and spaces from 12' x 12' to 18' x 18' for the 52" size.



SOFT WHITE (3000K)

BRIGHT WHITE (4000K)

DAYLIGHT (5000K)

Pull Chain Control

- Hi/ Med/ Low Speeds
- 3000K/ 4000K/ 5000K CCT
(light turns off between each color selection)

- MATTE WHITE
- DARK WOOD
- BLACK
- BRUSHED NICKEL/SILVER

Specifications

Blade Sweep	44"	52"
No. Blades	3	
Blade Material	ABS	
Down-rod (incl)	6"	
Sloped Ceiling Mount	Y - up to 18 degrees	
Remote Control	N	
Light Kit Included	Y	
Lens Material	PC	
Light Kit Wattage	18W LED	
Lumen Output	1000 lm	
Light Efficacy	56 LPW	
Light Dimmable	N	
Light Replaceable	N	
Selectable CCT	3000/4000/5000K	
CRI	≥ 90	
Motor Type	AC	
Max Motor Wattage	45W	65W
MAX RPM	210	160
No. Speeds	3	
Reversible	Y	
Airflow (CFM)	2986 (hi) 2196 (med) 1596 (lo)	4237 (hi) 3243 (med) 2543 (lo)
Airflow Efficiency	75 CFM/W (hi) 87 CFM/W (med) 114 CFM/W (lo)	85 CFM/W (hi) 106 CFM/W (med) 131 CFM/W (lo)
Indoor/ Outdoor	Indoor Only	
Wet Location Rated	N	
Certifications	ETL Listed for Dry Location	
Warranty	2 Years Limited, Lifetime for Motor	
Product Weight	11.1 lb	11.9 lb
Packaged Weight	15.4 lb	17.4 lb

Dimensions

Fan Diameter	44"		52"
Fan Height		14.6"	
Fan Blade Length	21.1"		25.1"
Fan Blade Width	4.7"		4.8"
Down-rod Length		6"	
Lead Wire Length		54"	
Package Size (in)	23.1 x 12.4 x 9.7		27.0 x 12.4 x 9.7



Mounting Notes:

- Down-rod mount only to flat or sloped ceilings
- Distance from ceiling to bottom of fan/light: 12.7"
- 54" Lead wire accommodates up to 48" down-rods (supplied by others)