

# INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later

## CAUTION

**WARNING:** Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

## GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

## ASSEMBLY AND INSTALLATION

1. Lock the loop(16) and Thinner tube (17) and Wider tube(18) on the nipple (19) of the fixture.
2. Attach mounting bar (6) with threaded nipple (10) to outlet box (1) secured with two box screws (9).
3. Attach quick links (15) to the hanging loop (12) and the appropriate amount of chain (14).
4. Secure the Loop (16) with Thinner Tube (17) and Wider Tube (18) to the Nipple (19)
5. Open the quick link (15) at the other end and then hook onto top of fixture (16), close the quick links.
6. Thread the wires through the chain and the hanging loop (12) up to outlet box.
7. Pull out the outlet wire and ground wire from the outlet box  
Make wire connections with wire nuts(5).  
--Ribbed wire (W/O marking) or white wire from light to White wire (2) from power source.  
--Smooth wire (W marking) or black wire from light to Black wire (3) from power source.  
--Attach the ground wire (4) to mounting bar (7) with a ground screw (8).
8. Raise canopy (11) against ceiling and lock it in position by Finial (13) .
9. Place the glass shade (20) onto the socket (21) then secure with socket sleeve(19).
11. Install bulbs: (bulbs not included)  
(Don't exceed the maximum capacity recommended on the sockets).

INSTALLATION IS NOW COMPLETED

