

Project:

Belle Flare Medium LED Bell Pendant Spec Sheet


SKU: 3533.03

Unmistakably modern, the pristine curved Belle Flare Pendant directs LED light downward through reflective radiance within the dome shade while subtly reflecting light upward through the flared trim at the top of the dome. Scaled for residential, hospitality and commercial settings for an enduring modern presence.

 $Learn\ more:\ \underline{https://sonnemanlight.com/belle-flare-pendant}$

Type #:





Dimensions

 Height:
 18"

 Diameter:
 19"

 Canopy/Backplate/Base:
 4.5"

 Hanging Details:
 20' Adjustable Cord

 Size:
 Medium

 Canopy/Backplate/Base Height:
 0.5"

Electrical Specs

 Bulb(s) Included?:
 Yes

 Bulb 1 Type:
 Integral LED

 Bulb Quantity:
 1

 Input Voltage:
 120-277VAC

 Initial Lumens:
 1680

 Color Temperature:
 3000K

 CRI:
 90

 Power Supply Type:
 Driver

 Power Supply Quantity:
 1

 Power Supply Location:
 Outlet Box

 Dimming Type:
 TRIAC/ELV/0-10V

 Bulb Max Wattage:
 16

Installation

Installation: Licensed electrician required Sloped Ceiling Compatible?: Not Compatible Cord Length: 20' Adjustable Cord Minimum Hanging Height: 19" Maximum Hanging Height: 258"

Shade

Shade Material: Metal Shade 1 Color: Satin White

General Listings

 Features:
 Damp Rated

 Certification:
 C-ETL-US

 Color/Finish:
 Satin White (.03)

 Dark Sky Friendly:
 NA

Available Finishes

Available Finishes: Brass Finish (.14), Satin Black (.25), Satin White (.03)

Available Color Temperatures

Available Color Temperatures: 3000k