

Assembly Instruction

Product SKU: WF3022T-5PK

Important Information

- Assembly requires at least two people.
- Assemble on a soft, flat surface (like a carpet) to prevent scratches.
- Do not fully tighten screws until all parts are in place.
- Carefully check all parts against the parts list.
- Keep all hardware and small parts away from children.

Hardware Kit

Part ID	Description	Qty
H1	Long Bolt (for table)	16
H2	Short Bolt (for chairs)	32
H3	Washer	48
H4	Allen Wrench	1

Table Parts

Part ID	Description	Qty
A	Tabletop	1
B	Table Leg	4

Chair Parts (for one chair)

Part ID	Description	Qty
C	Seat Cushion	1
D	Back Rest	1
E	Front Leg	2
F	Back Leg	2

Note: You will have parts for 4 chairs in total.

Assembly Steps

Table Assembly

Step 1: Attach Legs to Tabletop

Hardware Needed: (H1) Long Bolt x 16, (H3) Washer x 16

1. Place the **Tabletop (A)** upside down on a soft, clean surface.
2. Align one **Table Leg (B)** with the pre-drilled holes in one corner.
3. Insert four **Long Bolts (H1)** with **Washers (H3)** through the tabletop frame and into the leg.
4. Use the **Allen Wrench (H4)** to loosely tighten the bolts. Repeat for all four legs.

Step 2: Final Tightening (Table)

1. With assistance, carefully flip the table upright.
2. Check that the table is stable on a level surface.
3. Go back and fully tighten all 16 bolts securely with the **Allen Wrench (H4)**.

Chair Assembly (Repeat for all 4 Chairs)

Step 3: Attach Chair Legs

Hardware Needed per chair: (H2) Short Bolt x 8, (H3) Washer x 8

1. Attach the two **Front Legs (E)** to the underside of the **Seat Cushion (C)** using two bolts and washers per leg.
2. Attach the two **Back Legs (F)** to the underside of the **Seat Cushion (C)** using two bolts and washers per leg.
3. Do not fully tighten the bolts yet.

Step 4: Attach Back Rest & Final Tightening

Hardware Needed per chair: (H2) Short Bolt x 4, (H3) Washer x 4

1. Align the **Back Rest (D)** with the back legs and the seat frame.
2. Secure it using four **Short Bolts (H2)** and four **Washers (H3)**.
3. Place the chair upright on a level surface.
4. Fully tighten all 12 bolts on the chair securely.