

## Corner Sink Base Installation Instructions

### Tools Required:

Electric drill or screwdriver (cross)

Level

Woodworking glue (optional)

Cabinet connection screws

Tape measure

Silicone (for sink sealing)

### Package contents (subject to the actual product):

Left and right side panels × 1

Bottom panel × 1

Rear support bar × 2

Front frame/door panel × 1

Folding gusset (if any) × 1

Cabinet door × 1 – 2

Hinges and screw accessories

Reserved space required for sink installation

### Installation steps:

#### 1. Assemble the main cabinet structure

Assemble the bottom panel, two side panels and rear support bar in sequence to form an “L” shaped frame.

Use screws to secure all connection points to ensure stability.

Install the front frame (including the door frame), connect and tighten with screws.

#### 2. Install the corner plate (if any)

Install the gusset plate between the two inner corners to enhance the structural stability.

Adjust the angle and fix it.

#### 3. Install the cabinet door

Install the hinge to the back of the cabinet door and fix it to the cabinet frame according to the reserved holes.

Make sure the door gap is aligned and opens smoothly.

#### 4. Install the sink (if applicable)

Reserve a sink opening on the countertop and apply silicone to seal the edges before installing the sink.

Gently press the sink into the countertop opening and connect the drain pipe and faucet according to the instructions.

Ensure there is no water seepage and keep it level.

**Notes:**

The corner cabinet must be installed at the angle between the two walls to ensure accurate positioning.

Before installation, please confirm whether the position of the water pipe and sewer interface is appropriate.

After the sink is installed, the edges must be waterproof and sealed to prevent water seepage from damaging the cabinet.

It is not recommended for the cabinet to bear heavy stone countertops. If necessary, reinforce the support.