

Project:

Purolinear 360 LED Wall Bar Spec Sheet

SKU: 23QSWL244B120PHA Learn more at: https://sonnemanlight.com/purolinear-360-led-wall-bar

Description: A system of linear tubes, set within the geometry of surface-mounted cylinder brackets, rotate individually to direct the LED illumination in 360 degrees along their axis. Arranged in a linear pattern or along a single path, the possibilities for compositions are endless and unlimited in scalability. Set on a wall, in line behind a bed, the rotatable luminaires provide the variability of direct or indirect illumination.

Type #:

Dimensions

Height: 1.25" Width: 97.25" Extends: 2.75" Minimum Extension: 2.75 Maximum Extension: 2.75 Canopy/Backplate/Base: 4.5" Shape: Double Linear 48" Size: Canopy/Backplate/Base Depth: 0.5

Electrical Specs

Bulb(s) Included?: Yes Integral LED Bulb 1 Type: Bulb Quantity: Input Voltage: 120VAC Wattage: 13 Initial Lumens: 2240 **Delivered Lumens:** 1600 Color Temperature: 3000K 90 Power Supply Type: Driver Power Supply Quantity: Power Supply Location: **Outlet Box** TRIAC/ELV Dimming Type: Bulb Max Wattage: 13

Installation

Installation: Licensed electrician required

Shade

Shade 1 Material: Optical Acrylic

Available Finishes

Available Finishes: Polished Chrome (.01), Satin Black (.25), Satin Chrome (.23), Satin White (.03)

General Listings

Features:

Certification: Color/Finish:

Dark Sky Friendly:

ADA Compliant, Damp Rated C-ETL-US Satin White (.03) N