

$DEMILAV_{TM}$

Features

- KOHLER cast iron
- Self-rimming
- Without overflow
- · Less faucet drilling
- Countertop installation
- 18-1/4" (46.4 cm) x 15-5/8" (39.7 cm)


Codes/Standards Applicable

Specified model meets or exceeds the following:

- ICC/ANSI A117.1
- IAPMO/UPC
- ASME A112.19.1M
- CSA B45
- ADA

WADING POOL™ LAVATORY **K-2833**

ADA



Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Accessories:

- · CP: Polished Chrome
- Other: Refer to Price Book for additional colors/finishes

Specified Model

Model	Description	Colors/Finishes			
K-2833	Wading Pool lavatory	□ 0	☐ Other		
Recommended Accessories					
K-9018	Adjustable P-trap with extension	□ CP	☐ Other		
K-7126	Pop-up lavatory drain	□ СР	☐ Other		

Product Specification

The self-rimming cast iron lavatory shall be 18-1/4" (46.4 cm) in length, and 15-5/8" (39.7 cm) in width. Product shall be without overflow and less faucet drilling. Product shall be for countertop installation. Product shall be Kohler Model K-2833-_____.

DEMILAV_{TM}

Technical Information

Fixture*:		
Basin area	16-1/2" (41.9 cm) x 13-7/8" (35.2 cm)	
Water depth	5" (12.7 cm)	
Drain hole	1-3/4" (4.4 cm) D.	
* Approximate measurements for comparison only.		

Included component:	
Cut-out template	1046630-7

Installation Notes

Install this product according to the installation guide.

Product does not have overflow.

Select a faucet with a minimum spout reach of 5" (12.7 cm). Refer to the faucet rough-in dimensions to ensure the spout will reach over the lavatory rim into the basin.

The faucet spout must be tall enough to clear the 1-11/16'' (4.3 cm) rim height and provide a 1'' (2.5 cm) air gap per ASME A112.1.2.

NOTICE: The countertop manufacturer or cutter **must** use the cut-out template provided with the product, or a current cut-out template provided by the Kohler Co. (call 1-800-4-KOHLER). Kohler Co. is not responsible for cutout errors when the incorrect cut-out template is used.

