

ASSEMBLY AND INSTALLATION INSTRUCTIONS

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Before installing, consult local electrical codes for wiring and grounding requirement.

1. Thread 2 mounting screws properly into the 2 relevant mounting holes pre-drilled on the cross bar.
2. Attach the cross bar to outlet box using 2 outlet box screws upwards.
3. Weave fixture wires and ground wire through the every tube(A), swivel and canopy.
4. Make wire connections:
 - Attach ground wire to house ground wire using a wire nut or attach them to the cross bar with a green ground screw
 - Attach white wire from light to white wire from power source with a wire nut.
 - Attach black wire from light to black wire from power source with a wire nut.

Observing: positive wire with positive wire, negative wire with negative wire, ground wire with ground wire.

5. Tuck the wire connections neatly into the outlet box.
6. Attach the canopy to the ceiling and let the 2 mounting screws protrude through the 2 pre-drilled holes on the canopy and secure it with ball nuts.
9. Thread the nipple onto the coupler and thread the nut(A) onto the nipple. Let the tube, the pad (A) & pad(B) pass through the nipple, and thread the nut(B) onto the nipple. Put the glass shade, plastic pad, metal pad onto the nipple in turn, then thread the nut(C) onto the nipple. Finally put the cover onto the nipple, and secure it with finial.
10. Install bulb.(not included) (Please do not exceed the maximum capacity which is recommended on the fixture.)
11. Turn on the power at fuse or circuit box.

