

R4RD2L, R4SD2L

4.5" Volta - Downlight Invisible Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Volta LED downlight series represents an innovation in design and technology for architectural lighting. This high lumen and adaptable family of fixtures with a comprehensive set of round and square fittings, affords a sustainable solution for commercial, corporate, and upscale residential applications.

FEATURES

- 2" lens regress for superior glare control
- Field selectable light engine height for cut-off angle adjustment (30° - 34°) and accessory use
- Integral patterned tempered trim lens included standard
- Compatible with wide range of accessories
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction

Input: Universal 120 - 277V AC 50/60 Hz

Dimming: Electronic Low Voltage (ELV): 100%-5% (120V only)
0-10V: 100%-0% (120 - 277V)

Light Source: High output 3-step Mac Adam Ellipse COB
Rated life of 50,000 hours at L70

Mounting: Heavy gauge retention clips support trim firmly. Safety cabling standard.
Ceiling cut out (Round): Ø 5 1/8"
Ceiling cut out (Square): 5 1/8" x 5 1/8"
Accommodates 1/2" - 1 1/2" ceiling thickness

Finish: Electrostatically powder coated White, Black. Enamel coated Haze.

Standards: ETL & cETL Wet location Listed

TRIMS (ORDER HOUSING SEPARATELY)

Model	Beam Angle	Reference Output*			Color Temp	CRI	Finishes	Reflector/Trim
		Lumens	CBCP	Lumen/Watt				
 R4RD2L Round	S 15°	1391	12282	60	827 2700K 85 927 2700K 90 830 3000K 85 930 3000K 90 835 3500K 85 840 4000K 85	BK Black HZ Haze WT White		
	N 25°	2694	7980	75				
	F 45°	2609	4347	72				
	W 60°	2413	2679	67				
R4SD2L Square	S 15°	1398	12724	60				
	N 25°	2852	7634	79				
	F 45°	2785	4295	77				
	W 60°	2430	2422	68				

*Reference output shows **830**(85CRI 3000K) trim with **36** housing. Use multiplier table below to determine the output for other combinations.

Multiplier	TRIM					
	827	927	830	930	835	840
HOUSING 36	0.937	0.764	1.000	0.815	1.045	1.054
25	0.685	0.558	0.731	0.596	0.764	0.770
15	0.456	0.371	0.486	0.396	0.508	0.512

R4_D2L-_____ - _____

Example: **R4RD2L-S827-WT**

Please see next page for housing units(required)

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

R4RD2L, R4SD2L

4.5" Volta - Downlight Invisible Trim

WAC LIGHTING

Responsible Lighting®

HOUSINGS (REQUIRED)

		Model	Power*	S	N, F, W	Rating	Emergency Backup
<p>Round New Construction</p>	R4RNL	Airtight	15	10W	15W	IC rated	EM Emergency backup battery (OPTIONAL)
	R4RCL	Airtight, Chicago Plenum	25	15W	25W	IC rated	
			36	23W	36W	Non-IC	
<p>Square New Construction</p>	R4SNL	Airtight	15	10W	15W	IC rated	EM Emergency backup battery (OPTIONAL)
	R4SCL	Airtight, Chicago Plenum	25	15W	25W	IC rated	
			36	23W	36W	Non-IC	

*Power consumption depends on beam angle of the trim.

R4 _____ -
 Example: **R4RNL-15** or **R4RNL-15EM** (with Emergency backup battery)

Field Replaceable Driver

D-R4N-15	Driver for 15W New Construction Hsg
D-R4N-25	Driver for 25W New Construction Hsg
D-R4N-36	Driver for 36W New Construction Hsg

Invisible Trim housings come included with die-cast spackle frame.

FIELD CHANGEABLE GLARE CONTROL AND OPTIC SYSTEM

Accessory holder
 Holds up to two lenses or
 One lens and one glare control

Optical cartridge
 Allows tool-less exchange of reflectors



Reflector
 For narrow flood, flood, and wide flood.
 Spot distribution features dedicated module.

Accessory holder	
LENS-73-HLD	Required to hold lens and glare control accessories
Glare control accessories	
LENS-73-HCL LENS-73-CRL	Honeycomb Louver Cross Louver

Lens	
LENS-73-AMB LENS-73-RED LENS-73-FR LENS-73-SPR LENS-73-BEL	Amber lens Red lens Frosted lens Spread lens Beam Elongating

Interchangeable Reflector	
REF-R4-N REF-R4-F REF-R4-W	Narrow beam reflector Flood beam reflector Wide beam reflector

waclighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760