



Dundalk LeisureCraft Tiki Bar Assembly



Your Tiki Bar will arrive partially assembled. The bar base is assembled. All you need to do is attach the bar top and assemble and attach the roof, and assemble the stools.

Required:

- 2 people (recommended)
- Rubber Mallet
- Cordless Drill (we supply the bit)

Hardware packet:

1½" brown ceramic-coated deck screws,
4" brown ceramic-coated deck screws,
¾" zinc-plated flat-head wood screws,
1½" Tin-plated Kreg screws (not shown)
Nylon Cable Clamps.
#2 Robertson screwdriver bit



Place the bar base in position and fit the bar top over the base as shown.

Insert the roof post assemblies into the two holes on the top of the bar all the way until they hit bottom.

Roof:

Lay-out the roof parts as shown on the left.

Insert the tenons into the holes, and use a rubber mallet to tap them in securely, as shown below.





Fasten the six horizontal roof slat boards as shown, with one 1½” deck screw per joint.

Lay a piece of roof thatch in place, and attach it with supplied ¾” wood screws and nylon cable clamps close to each end and two places in the middle evenly spaced out. (4 places)

Also fasten the thatch onto the bottom slat using cable clamps wrapped around the netting of the thatch as shown (4 places).

Repeat for the other side of the roof.



Set the assembled roof top on top of the roof posts and fasten with 4” deck screws, (4 places) as shown.



...View Assembly Video online:

<https://www.youtube.com/watch?v=KLe-pounehU...>

YouTube

or



Scan this QR code to watch the Assembly Video on YouTube

Manufactured by:

Dundalk LeisureCraft Inc
318448 8th Line NE,
Dundalk, Ontario Canada
L9V 2K3

Phone: (888)923-9813
www.dundalkleisurecraft.com
www.leisurecraftusa.com