


USE & CARE MANUAL

PRODUCT DESCRIPTION

GETPRO fireclay kitchen sink is made from 100% natural materials FIRECLAY, is the most durable material for high-end quality kitchen sinks, every GETPRO kitchen sink is fired at extremely high temperatures with a premium glaze in its overall kitchen sink to repel stains, prolonging the lifetime of its use. The solid core construction makes our sink superior strengthened and durable enough to withstand heavy-duty use, It's highly resistant to impact, thermal shock, crack, and scratch. GETPRO fireclay sink is durable, non-discoloring, and easy to maintain for several dozen years.

USE & CARE GUIDE




In order to clean the kitchen sink, please only use a soft cotton cloth or soft sponge.



Never use acidic, alkali, or any products to clean the kitchen sink that state on their label that they are Not Suitable for use on ceramics.



To clean inside the kitchen sink, fill it with warm water and add a couple of squirts of dish liquid. Allow it to sit for 30 minutes. Let the kitchen sink drain and wipe away any residue.



In order to remove light marks or scratches, apply toothpaste to the area and scrub with a soft cloth or sponge.



If deep cleaning is necessary, rinse or soak the kitchen sink in warm water for 30 minutes and add a bit of liquid soap or dish soap to the water. Rinse and dry with a soft towel.



It is advised to clean the surface of the kitchen sink regularly in order to remove any insoluble products. Warm soapy water should be used and afterwards the kitchen sink should be wiped. Do not let cleaners soak in.



The surface of the kitchen sink has good resistance properties to acids, but should not come into contact with alkalis or organic solvents, such as caustic soda, some multi-surface cleaners, bathroom cleaners, bleaches, harsh solvents, burning cigarettes, strong chemicals such as dry-cleaning fluids, paint strippers, acetone, citrus based chemicals, and nail/varnish removers.



Please read all instructions carefully before proceeding with installation.



Due to the complexity of the installation procedure, a professional plumber is required.

SCRATCH REMOVAL

- To eliminate minor scratches, apply a thin layer of automotive paste wax and lightly buff the affected area with a clean cloth.
- To address small scratches, use wet/dry sandpaper with a 600-grit rating to lightly sand the surface.
- For repairing deep scratches on your kitchen sink, opt for higher-grit sandpaper, such as 1,500-grit wet/dry sandpaper. Start by moistening the sandpaper, and then use gentle circular movements to rub it over the affected area until the scratches vanish. Make sure to sand the surrounding area as well to blend the repair seamlessly and achieve an even surface.
- After sanding, use a towel to wipe away any dust from the sandpaper and dry the kitchen sink surface. Then, apply a quarter-size amount of automotive polishing compound onto a separate washcloth. Rub the compound gently in circular motions over the kitchen sink until the sanded ceramic surface shines and no residue of the compound remains.

STAIN REMOVAL

- Mix one cup of water and one cup of vinegar together, then add two tablespoons of baking soda. Transfer the solution into a spray bottle and adjust the concentration by adding additional water if needed. Spray the affected area and let the solution sit for five to seven minutes.
- For stubborn stains, directly apply a tablespoon of baking soda onto the stain and use a soft-bristled brush or disposable toothbrush to scrub it away. After cleaning the entire kitchen sink, rinse it thoroughly with water.