

Project Name

Location

Prepared By



## SATCO 67-510

EX COMBO-CAN

### Notes

(www) 05-19-2023 00:30:24

### General

|                           |           |
|---------------------------|-----------|
| Status                    | Active    |
| Fixture Type              | Exit Sign |
| Finish                    | White     |
| Wattage                   | 3W        |
| Lumen Output              | 120L      |
| CCT (Kelvin)              | 5700K     |
| IP Rating                 | IP40      |
| Indoor or Outdoor Fixture | Indoor    |

### Specifications

|                       |                                 |
|-----------------------|---------------------------------|
| Technology            | LED                             |
| CRI                   | 80+                             |
| Voltage               | 120V-347V                       |
| Operating Temperature | +10C (+50F) to +40C (+104F)     |
| Dimmable              | Non-Dimmable                    |
| Lens Material         | Polycarbonate (PC)              |
| Surge Protection      | Built-in surge protection - 6KV |
| Weight (lb.)          | 3.31                            |
| Material              | Thermoplastic                   |

### Dimensions

|                 |      |
|-----------------|------|
| Extension (in.) | 2.58 |
|-----------------|------|

### Compliance

|                            |               |
|----------------------------|---------------|
| Safety Listing             | CSAus         |
| Location Rating            | Damp          |
| California Status          | Non-Compliant |
| Title 20 / 24 Status       | Non-Compliant |
| RoHS Compliant             | Yes           |
| Canadian Standard ICES-005 | Class B       |
| SDS Sheet                  | LED_Fixture   |

### Additional Information

|                    |                                                                  |
|--------------------|------------------------------------------------------------------|
| Specification Note | Ni-Cad Battery; 120 minute discharge time; 24 Hour Recharge Time |
| Warranty           | 5-Years                                                          |