


ASSEMBLY AND INSTALLATION INSTRUCTIONS

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.


NOTES:

1. Before installing, consult local electrical codes for wiring and grounding requirements.
2. Read and save these instructions.
3. Always switch off the electricity supply and allow to cool for 10 minutes before changing the light bulbs.

1-LIGHT MINI PENDANT



TOOLS REQUIRED



PREPARATION

Before beginning assembly of product, make sure all parts are present. Compare parts with package contents list and hardware contents list. If any part is missing or damaged, do not attempt to assemble the product. When the lamp is not installed finish, please don't throw away the package, so as not to leave the parts in the package.


PART LIST AND HARDWARE LIST

PIECE	DESCRIPTION	QUANTITY
A	Cross bar	1
B	Green ground screw	1
C	Outlet box screw	2
D	Wire nut	3
E	Canopy screw	2

PIECE	DESCRIPTION	QUANTITY
F	Canopy	1
G	12"tube	3
H	6"tube	1
I	Metal shade	1
J	Fixture body	1

INSTALLATION

1. Attach the 6"tube(H) through the wire to fixture body(I), and lock the 12"tube (G) and 6"tube (H) in turn.
2. Attach the metal shade(I) through the tube(G) (H),attach the notch(I1) of the metal shade to the fixture body (J).
3. Attach the swivel(F1) through wire to 12"tube(G).
4. Attach the cross bar (A) to the junction box with outlet box screw (C).
5. Attach the supply circuit ground wire (green or bare copper wire) to the the fixture ground wire,black to (black) and white to (white).



6. Attach the canopy (F) to the cross bar (A), secure with canopy screw (E)
7. Install the 60W MAX ST64 Bulb (not included) into socket.

