

# WAC LIGHTING

## Ion 2" Square 5CCT

### New Construction Downlight

Fixture Type: \_\_\_\_\_  
Catalog Number: \_\_\_\_\_  
Project: \_\_\_\_\_  
Location: \_\_\_\_\_

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R2DSDN	F 35°	9CS 2700K/3000K/3500K/4000K/5000K - 90	695	2140	WT White

Example: **R2DSDN-F9CS-WT**

#### DESCRIPTION

Minimum profile downlight with remote driver included for easy remodel or new construction installation.

#### FEATURES

- 5-CCT Switchable between 2700K and 5000K
- Sold as new construction, may be configured in field for remodel
- Driver included
- 5 year warranty

#### SPECIFICATIONS

<b>Construction</b>	Die-cast Aluminum with 20-gauge Cold Rolled Steel Driver Box
<b>Power:</b>	9W
<b>Input:</b>	120 VAC, 50/60Hz
<b>Dimming:</b>	ELV: 100-10% , TRIAC: 100-5%
<b>Light Source:</b>	Integrated LED
<b>Lens:</b>	Frosted TIR Lens
<b>Rated Life:</b>	50,000 Hours
<b>Mounting:</b>	New construction housings included with hanger bars
<b>Cut Out:</b>	3"
<b>Finish:</b>	Electrostatically Powder Coated: White
<b>Ceiling Thickness:</b>	1/2" - 1 1/2"
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	ETL, cETL, Title 24 JA8 Compliant, Airtight, IC



#### FINISHES:



White

#### LINE DRAWING

