## New! SOSS **Hercules Hinge**<sup>®</sup>

The new SOSS Hercules Hinges® are ideal for doors of extreme weight or size. They can be used in place of standard model #218 or #220 invisible hinges when the use of fewer hinges is needed.

For example, a standard 80" tall, 36" wide, 1-3/4" door that weighs 150 lbs. normally needs four model #218 SOSS Invisible Hinges. With the SOSS Hercules Hinge® model #218H on this size door, only two hinges are required.

Hinges, please consult the factory.

Sousi Contract of the contract						
SOSS Hercules Hinges are currently available in three popular finishes; Satin Chrome (US26D), Satin Brass	Hinge #	Description	Door Material	Fire Rating*	Min. Door Thickness	
(US4), and Satin Nickel (US15).	218H	Solid alloy steel body & links, similar to model #218	Wood/Metal	2 Hour	13⁄4"	
For assistance with choosing the correct number of SOSS Hercules	220H	Solid alloy steel body & links, similar to model #220	Wood/Metal	2 Hour	2"	

\*Rating is in accordance with BS EN 1634-1 standards. These hinges are not UL fire rated.

soss Invisible Hinge

## This sizing chart is intended for doors that exceed sizing chart on page 51.

Door Width in Inches and Millimeters					
in	mm				
4 — 100					
5	_				
=	— 200				
10 —	300				
15—	400				
20 —	— 500 —				
30—	——700 —				
40-	— 900 —				
50— 60—	1,250				
70——	1,750 2,000				


Daar W. dala

Example: A 60" wide door weighing 300 lbs. would require four #218H or three #220H Hercules Hinges. The red line shows how the sizing and selection were determined from the sizing chart.

	Hinge Number	218H	220H
	Number of Hinges Required	12	10
Door \ Pour Kilo	les Hinge Veight in nds and grams		
kg 495 —	lb 1089	11	9
440 450	990 968	10	8
385 <del>-</del>	847	9	7
330 — 315	726 693	8	_
275 <sub>270</sub>	594 605	7	6
220 225	404	6	5
180 165 — 135	363	5	4
110 — 90	198	4	
		3	3
			2
		2	

Dimension	218H	220H
A	11/8" (28.58 mm)	1%" (34.93 mm)
В	<sup>55</sup> / <sub>64</sub> " (21.83 mm)	11/16" (26.99 mm)
С	4 <sup>3</sup> % <sub>4</sub> " (117.08 mm)	5½" (139.70 mm)
D	<sup>23</sup> / <sub>64</sub> " (9.13 mm)	½" (12.70 mm)
E	1/4" (6.35 mm)	%2" (7.14 mm)
F	27/16" (61.91 mm)	2 <sup>3</sup> / <sub>32</sub> " (75.41 mm)
G	1/16" (1.59 mm)	3/32" (2.38 mm)
Н	141/64" (41.67 mm)	163/64" (50.40 mm)
1	<sup>13</sup> / <sub>32</sub> " (10.32 mm)	<sup>15</sup> / <sub>32</sub> " (11.91 mm)
Minimum Material Thickness	1¾" (44.45 mm)	2" (50.80 mm)
Wood Screw Sizes	#10 x 2½"	#12 x 2½"
Soft Wood Pilot Hole	No.43	No. 38
Hard Wood Pilot Hole	No. 31	No. 25
Machine Screw Size	#10-24 x ¾"	#12-24 x 1"
Hinge Weight	2.15 lbs	3.80 lbs.

## **KEY TO DIMENSIONS SHOWN IN CHARTS**



All SOSS Hercules Hinges are shipped with the proper size wood and machine screws unless ordered without. Do not exceed "E" dimension.